

## DF9

Reference number of the Declaration of Performance: 4462500

1. Unique ID code of the product type	DF9
2. Application(s)	Liquid applied water impermeable dispersion product Outdoor area
3. Manufacturer	BOTAMENT GmbH Am Kruppwald 1 46238 Bottrop
4. Authorized representative	-
5. System of AVCP	System 3
6. Harmonised standard	DIN EN 14891: 2012
7. Notified body	MPA Braunschweig ID code NB 0761

8. Declared performances


Essential characteristic	Performance	AVCP	harmonised technical specification
Initial tensile adhesion strength	≥ 0.5 N/mm <sup>2</sup>	System 3	DIN EN 14891: 2012
Water impermeability	no penetration		
Tensile adhesion strength after water contact	≥ 0.5 N/mm <sup>2</sup>		
Tensile adhesion strength after heat ageing	≥ 0.5 N/mm <sup>2</sup>		
Tensile adhesion strength after freeze-thaw cycles	≥ 0.5 N/mm <sup>2</sup>		
Tensile adhesion strength after contact with lime water	≥ 0.5 N/mm <sup>2</sup>		
Crack bridging ability in standard conditions	≥ 0.75 mm		

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr. Oliver Wowra  
Technical Director Botament

Bottrop, 14.09.2023  
(place and date of issue)

  
(signature)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.