

Safety data sheet
according to UK REACH

Printing date 11.07.2025

Version number 49 (replaces version 48)

Revision: 11.07.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name** **EKF 500 - Komponente A**

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

· **Application of the substance / the mixture**

Sealing mortar

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:** BOTAMENT Systembaustoffe
Am Kruppwald 1
D-46238 Bottrop

Tel.: ++49(0)2041 101-90
Fax.: ++49(0)2041 101-988

· **Informing department:**

Product safety department.
msds@botament.com

· **1.4 Emergency telephone number:**

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Skin Irrit. 2 H315 Causes skin irritation.
Eye Dam. 1 H318 Causes serious eye damage.
Skin Sens. 1 H317 May cause an allergic skin reaction.
Repr. 1A H360F May damage fertility.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· **2.2 Label elements**

· **Labelling according to**

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**



GHS05 GHS07 GHS08

· **Signal word**

Danger

· **Hazard-determining components of labelling:**

1,4-bis(2,3-epoxypropoxy)butane
4,4'-Methylenediphenyldiglycidyl ether
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] bis(oxirane) and 2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane

(Contd. on page 2)

**Safety data sheet
according to UK REACH**

Printing date 11.07.2025

Version number 49 (replaces version 48)

Revision: 11.07.2025

Trade name EKF 500 - Komponente A

(Contd. of page 1)

- **Hazard statements**
 - H315 Causes skin irritation.
 - H318 Causes serious eye damage.
 - H317 May cause an allergic skin reaction.
 - H360F May damage fertility.
 - H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
 - P101 If medical advice is needed, have product container or label at hand.
 - P102 Keep out of reach of children.
 - P103 Read carefully and follow all instructions.
 - P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 - P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - P310 Immediately call a POISON CENTER/doctor.
 - P321 Specific treatment (see on this label).
 - P362+P364 Take off contaminated clothing and wash it before reuse.
 - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 1675-54-3	4,4'-Methylenediphenyldiglycidyl ether Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥10-<25%
CAS: 1317-65-3 EINECS: 207-439-9	CALCIUM CARBONATE substance with a Community workplace exposure limit	10-30%
CAS: 9003-36-5	Reaction mass of 2, 2'-[methylenebis(2, 1-phenyleneoxymethylene)]bis(oxirane) and 2, 2'-[methylenebis(4, 1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥2.5-<10%
CAS: 2425-79-8	1,4-bis(2,3-epoxypropoxy)butane Repr. 1A, H360F; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥3-<5%

- **Additional information** For the wording of the listed hazard phrases refer to section 16.

GB

(Contd. on page 3)

**Safety data sheet
according to UK REACH**

Printing date 11.07.2025

Version number 49 (replaces version 48)

Revision: 11.07.2025

Trade name EKF 500 - Komponente A

(Contd. of page 2)

SECTION 4: First aid measures

4.1 Description of first aid measures

- **General information** Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.
- **After inhalation** Supply fresh air; seek medical advice if symptoms occur. If unconscious, place in recovery position and seek medical advice.
- **After skin contact** In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
- **After eye contact** Rinse opened eye for several minutes under running water. Call a doctor immediately
- **After swallowing** Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.

4.2 Most important symptoms and effects, both acute and delayed

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:** Do not allow to enter drainage system, surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

GB

(Contd. on page 4)

**Safety data sheet
according to UK REACH**

Printing date 11.07.2025

Version number 49 (replaces version 48)

Revision: 11.07.2025

Trade name EKF 500 - Komponente A

(Contd. of page 3)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Open and handle containers with care. Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms), because the occupational exposure limit values (see chapter 8) could be exceeded. This must be avoided. Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.

Information about protection against explosions and fires:

Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and containers:

No special requirements.

Further information about storage conditions:

None.

Storage class

6.1C

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with critical values that require monitoring at the workplace:

CAS: 1317-65-3 CALCIUM CARBONATE

WEL Long-term value: 10* 4** mg/m³
*inhalable dust; **respirable

DNELs

CAS: 1317-65-3 CALCIUM CARBONATE

Oral DNEL 6.1 mg/kg bw/Tag (ArL)

Inhalative DNEL 10 mg/m³ (ArL)

CAS: 2425-79-8 1,4-bis(2,3-epoxypropoxy)butane

Dermal DNEL 9.26 mg/kg bw/day (ArL)

Inhalative DNEL 1.63 mg/m³ (ArL)

PNECs

CAS: 1317-65-3 CALCIUM CARBONATE

PNEC 100 mg/l (Sewage Treatment Plant)

(Contd. on page 5)

**Safety data sheet
according to UK REACH**

Printing date 11.07.2025

Version number 49 (replaces version 48)

Revision: 11.07.2025

Trade name EKF 500 - Komponente A

(Contd. of page 4)

CAS: 2425-79-8 1,4-bis(2,3-epoxypropoxy)butane

PNEC	0.024 mg/l (Fresh water)
	0.0024 mg/l (Mew)

- **Additional information:** *The lists that were valid during the compilation were used as basis.*
- **8.2 Exposure controls**
- **Appropriate engineering controls** *No further data; see section 7.*
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures** *Keep away from food, drink and animal feed.
Remove soiled, soaked clothing immediately.
Wash hands before breaks and at the end of work.
Avoid contact with eyes and skin.*
- **Breathing equipment:** *If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.*
- **Hand protection** *Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*
- **Material of gloves** *You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>
For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.
Nitrile rubber
Recommended material thickness: ≥ 0.4 mm*
- **Penetration time of glove material** *The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.
The following applies to all other gloves:
The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.
Nitrile rubber
Material thickness: ≥ 0.40 mm
Penetration time: ≥ 480 min
Butyl rubber:
Material thickness: ≥ 0.5 mm
Penetration time: ≥ 480 min*
- **Eye/face protection** *Tight-fitting safety goggles.
Safety goggles.*
- **Body protection:** *Protective clothing
Suitable protective clothing should be worn when working with*

(Contd. on page 6)

**Safety data sheet
according to UK REACH**

Printing date 11.07.2025

Version number 49 (replaces version 48)

Revision: 11.07.2025

Trade name EKF 500 - Komponente A

(Contd. of page 5)

epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour:	light yellow
· Smell:	Weak, characteristic
· Melting point/freezing point:	Not determined
· Boiling point or initial boiling point and boiling range	>200 °C (CAS: 25068-38-6 Propyl -2,2-diphenyl-4,4'dipropylloxirane polymers and homologues molecular weight < 700)
· Flash point:	151 °C
· Auto-ignition temperature:	184 °C
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· dynamic:	Not determined.
· Solubility	
· Water:	Not miscible or difficult to mix
· Steam pressure at 20 °C:	<0.1 hPa (CAS: 25068-38-6 Propyl -2,2-diphenyl-4,4'dipropylloxirane polymers and homologues molecular weight < 700)
· Density and/or relative density	
· Density at 20 °C	1.84 g/cm ³

· 9.2 Other information

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.

· Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void

(Contd. on page 7)

Safety data sheet
according to UK REACH

Printing date 11.07.2025

Version number 49 (replaces version 48)

Revision: 11.07.2025

Trade name EKF 500 - Komponente A

(Contd. of page 6)

· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether

Oral	LD50	11400 mg/kg (rat)
Dermal	LD50	23000 mg/kg (rabbit)
		>2000 mg/kg (rat)

CAS: 1317-65-3 CALCIUM CARBONATE

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl} oxirane

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

CAS: 2425-79-8 1,4-bis(2,3-epoxypropoxy)butane

Oral	LD50	1134 mg/kg (rat)
------	------	------------------

(Contd. on page 8)

**Safety data sheet
according to UK REACH**

Printing date 11.07.2025

Version number 49 (replaces version 48)

Revision: 11.07.2025

Trade name EKF 500 - Komponente A

(Contd. of page 7)

Dermal LD50 >2150 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** May damage fertility.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether

LC50/72h	>11 mg/l (algae)
IC50	>42.6 mg/l (Bak)
LC50/96h	2 mg/l (Oncorhynchus mykiss) 1.3 mg/l (fish)
EC50/48h	2.1 mg/l (daphnia) 1.8 mg/l (Daphnia magna)
ErC50/72h	11 mg/l (Selenastrum capricornutum)

CAS: 1317-65-3 CALCIUM CARBONATE

EC50/72h	>14 mg/l (Desmodesmus subspicatus)
LC50/96h	>10000 mg/l (Oncorhynchus mykiss)
LC50/48h	>1000 mg/l (Daphnia magna)
EC50/48h	>1000 mg/l (Daphnia magna)

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl} oxirane

LC50/96h	>100 mg/l (Daphnia magna)
EC50/96h	>100 mg/l (Leucidus idus)

CAS: 2425-79-8 1,4-bis(2,3-epoxypropoxy)butane

LC50/72h	160 mg/l (Pseudokirchneriella subcapitata)
EC50/24h	76 mg/l (Daphnia magna)

· **12.2 Persistence and degradability**

No further relevant information available.

(Contd. on page 9)

**Safety data sheet
according to UK REACH**

Printing date 11.07.2025

Version number 49 (replaces version 48)

Revision: 11.07.2025

Trade name EKF 500 - Komponente A

(Contd. of page 8)

- **12.3 Bioaccumulative potential** *No further relevant information available.*
- **12.4 Mobility in soil** *No further relevant information available.*
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*
- **12.6 Endocrine disrupting properties** *The product does not contain substances with endocrine disrupting properties.*
- **12.7 Other adverse effects**
- **Remark:** *Harmful to fish*
- **Additional ecological information:**
- **General notes:** *Harmful to aquatic organisms
Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.*

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** *Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- **Uncleaned packagings:**
- **Recommendation:** *Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.*

SECTION 14: Transport information

- | | |
|---|-----------------|
| <ul style="list-style-type: none"> · 14.1 UN number or ID number · ADR, ADN, IMDG, IATA | Void |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA | Void |
| <ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR, ADN, IMDG, IATA · Class | Void |
| <ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA | Void |
| <ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: | No |
| <ul style="list-style-type: none"> · 14.6 Special precautions for user | Not applicable. |
| <ul style="list-style-type: none"> · 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. |

(Contd. on page 10)

**Safety data sheet
according to UK REACH**

Printing date 11.07.2025

Version number 49 (replaces version 48)

Revision: 11.07.2025

Trade name EKF 500 - Komponente A

(Contd. of page 9)

· **UN "Model Regulation":** Void

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture**
- **Poisons Act**

No further relevant information available.

- **Regulated explosives precursors**

None of the ingredients is listed.

- **Regulated poisons**

None of the ingredients is listed.

- **Reportable explosives precursors**

None of the ingredients is listed.

- **Reportable poisons**

None of the ingredients is listed.

- **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H360F May damage fertility.
H411 Toxic to aquatic life with long lasting effects.

- **Department issuing data specification sheet:**

Environment protection department.

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)

(Contd. on page 11)

Safety data sheet
according to UK REACH

Printing date 11.07.2025

Version number 49 (replaces version 48)

Revision: 11.07.2025

Trade name EKF 500 - Komponente A

(Contd. of page 10)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Repr. 1A: Reproductive toxicity – Category 1A

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the
previous version altered.**