

# MC-Spezialspritze



## Technische Eigenschaften

|                                    |                                      |                       |  |
|------------------------------------|--------------------------------------|-----------------------|--|
| Material                           | Polyesterbeschichteter Stahlbehälter | Düsenpaket inklusive  | Flachstrahldüse, Rundstrahldüse  |
| Abmessung (Außendurchmesser, Höhe) | ca. 260 x 500 mm                     | Sprühlanze            | 50 cm  |
| Volumen                            | 6,0 L                                | Spiralschlauch        | 2,5 m  |
| Gewicht                            | 4,8 kg                               | Weitere Eigenschaften | <ul style="list-style-type: none"><li>• Integriertes Druckluft-Füllventil</li><li>• Bestücktes Ersatzteilstück am Gerät</li><li>• Manometer</li><li>• Schultergurt</li></ul> |
| Betriebsdruck                      | 6 bar                                |                       |  |

Reinigung: Nach Arbeitsabschluss und bei längeren Verarbeitungspausen ist die Pumpe gründlich mit Wasser zu spülen; während Verarbeitungspausen ist die Düse in Wasser zu lagern.

## Geeignete Produkte und Produktgruppen

|                 |                 |
|-----------------|-----------------|
| Ortolan Basic   | Emcoril Protect |
| Ortolan Classic | Emcoril Traffic |
| Ortolan Extra   | Emcoril Compact |
| Ortolan Premium | MC-Estrifan SI  |
| Ortolan Bio     | Emcephob        |
| Intaktin        |                 |

EXPERTISE  
CURING & RELEASE AGENTS

MC-Bauchemie Müller GmbH & Co. KG · Am Kruppwald 1-8 · 46238 Bottrop, Deutschland · Tel. +49 2041 101-50  
CI@mc-bauchemie.de · www.mc-bauchemie.de



BE SURE. BUILD SURE.

# MC-Spezialspritze



## Technical Data

|                                    |                             |                       |  |
|------------------------------------|-----------------------------|-----------------------|--|
| Material                           | Polyester-coated steel tank | Spray nozzles         | Flat spray nozzle, round spray nozzle  |
| Dimension (Outer diameter, Height) | approx. 260 x 500 mm        | Spray lance           | 50 cm  |
| Volume                             | 6.0 L                       | Spiral hose length    | 2.5 m  |
| Weight                             | 4.8 kg                      | Other characteristics | <ul style="list-style-type: none"><li>• Integrated compressed air filler valve</li><li>• Spare part's compartment</li><li>• Pressure gauge</li><li>• Shoulder straps</li></ul> |
| Operating pressure                 | 6 bar                       |                       |  |

Cleaning: After work and during long breaks please clean the pump with water; during processing breaks keep the nozzle in water.

## Suitable products and groups

|                 |                 |
|-----------------|-----------------|
| Ortolan Basic   | Emcoril Protect |
| Ortolan Classic | Emcoril Traffic |
| Ortolan Extra   | Emcoril Compact |
| Ortolan Premium | MC-Estrifan SI  |
| Ortolan Bio     | Emcephob        |
| Intaktin        |                 |

EXPERTISE  
CURING & RELEASE AGENTS

MC-Bauchemie Müller GmbH & Co. KG · Am Kruppwald 1-8 · 46238 Bottrop, Germany · Tel. +49 2041 101-50  
CI@mc-bauchemie.com · www.mc-bauchemie.com



BE SURE. BUILD SURE.