



BE SURE. BUILD SURE.

Page 1/14

## Safety data sheet according to UK REACH

Printing date 17.04.2026

Version number 14 (replaces version 13)

Revision: 17.04.2026

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name** **MC-DUR 1321 flex - Komponente B**

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Sector of Use** SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Application of the substance / the mixture**

Epoxy coating  
Hardening agent/ Curing agent

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:** MC-Bauchemie Müller GmbH & Co. KG  
Am Kruppwald 1-8  
D-46238 Bottrop  
Tel.: +49(0)2041-101-0  
Fax.: +49(0)2041-101-400  
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG  
Siloring 8  
CH-5606 Dintikon  
Tel. +41 56 616 68 68  
Fax +41 56 616 68 69

· **Informing department:** msds@mc-bauchemie.de

· **1.4 Emergency telephone number:**

Tel.: +49 / (0)700 24112112 (MCR)  
Tel.: +1 872 5888271 (MCR)

### SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

· **2.2 Label elements**

· **Labelling according to**

**Regulation (EC) No 1272/2008** The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**



GHS05 GHS07 GHS09

· **Signal word**

Danger

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

## Safety data sheet according to UK REACH

Printing date 17.04.2026

Version number 14 (replaces version 13)

Revision: 17.04.2026

**Trade name MC-DUR 1321 flex - Komponente B**

(Contd. of page 1)

- **Hazard-determining components of labelling:** Polyoxypropylenediamine  
decarboxylating cashew nut shell liquid  
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine
- **Hazard statements** H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H410 Very toxic to aquatic life with long lasting effects.
- **Precautionary statements** P260 Do not breathe dusts or mists.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER/doctor.  
P321 Specific treatment (see on this label).  
P362+P364 Take off contaminated clothing and wash it before reuse.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable
- **vPvB:** Not applicable

### SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 9046-10-0 Reg.nr.: 01-2119557899-12	Polyoxypropylenediamine Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Chronic 3, H412	30-60%
CAS: 9046-10-0	Polyoxypropylenediamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Aquatic Chronic 3, H412	≥25-≤30%
CAS: 93281-16-4 EINECS: 297-029-6	Phenol, reaction products with divinylbenzene Aquatic Chronic 3, H412	≥10-<25%
CAS: 8007-24-7 EINECS: 232-355-4	decarboxylating cashew nut shell liquid Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥3-<10%
CAS: 90-72-2 EINECS: 202-013-9 Reg.nr.: 2119560597-27	2,4,6-Tri-(dimethylaminomethyl)phenol Skin Corr. 1C, H314; Eye Dam. 1, H318; Acute Tox. 4, H302	≥5-<10%
CAS: 61788-46-3 EINECS: 262-977-1 Reg.nr.: 2119473798-17	alkylamine STOT RE 2, H373; Asp. Tox. 1, H304; Skin Corr. 1B, H314; Aquatic Chronic 1, H410 (M=10); Acute Tox. 4, H302; STOT SE 3, H335	≥5-<10%

(Contd. on page 3)



BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 17.04.2026

Version number 14 (replaces version 13)

Revision: 17.04.2026

Trade name **MC-DUR 1321 flex - Komponente B**

(Contd. of page 2)

CAS: 15520-10-2 EINECS: 239-556-6	2-Methylpentamethylenediamine Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; STOT SE 3, H335	≥1-<5%
CAS: 25513-64-8 EINECS: 247-063-2 Reg.nr.: 01-2119560598-25	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine Skin Corr. 1A, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317	≥1-<3%
	Polyamine adduct Eye Dam. 1, H318; Skin Irrit. 2, H315	≥1-<1.5%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

· **4.1 Description of first aid measures**

- **General information** Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.
- **After inhalation** Supply fresh air; seek medical advice if symptoms occur. If unconscious, place in recovery position and seek medical advice.
- **After skin contact** In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
- **After eye contact** Rinse opened eye for several minutes under running water. Call a doctor immediately
- **After swallowing** Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.

· **4.2 Most important symptoms and effects, both acute and delayed**

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

#### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

#### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)



BE SURE. BUILD SURE.

Page 4/14

## Safety data sheet according to UK REACH

Printing date 17.04.2026

Version number 14 (replaces version 13)

Revision: 17.04.2026

**Trade name MC-DUR 1321 flex - Komponente B**

(Contd. of page 3)

- **6.2 Environmental precautions:** *Inform respective authorities in case product reaches water or sewage system.  
Dilute with much water.*
- **6.3 Methods and material for containment and cleaning up:** *Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralising agent.  
Dispose of contaminated material as waste according to item 13.  
Ensure adequate ventilation.*
- **6.4 Reference to other sections** *See Section 7 for information on safe handling  
See Section 8 for information on personal protection equipment.  
See Section 13 for information on disposal.*

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** *Open and handle containers with care.  
Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms), because the occupational exposure limit values (see chapter 8) could be exceeded. This must be avoided.  
Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.  
Store in cool, dry place in tightly closed containers.*
- **Information about protection against explosions and fires:** *Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.*
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** *No special requirements.*
- **Further information about storage conditions:** *None.*
- **Storage class** *8B*

GB

(Contd. on page 5)



BE SURE. BUILD SURE.

**Safety data sheet  
according to UK REACH**

Printing date 17.04.2026

Version number 14 (replaces version 13)

Revision: 17.04.2026

**Trade name MC-DUR 1321 flex - Komponente B**

(Contd. of page 4)

**SECTION 8: Exposure controls/personal protection**

- **8.1 Control parameters**
- **Components with critical values that require**

**monitoring at the workplace:** *The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.*

· **DNELs**

**CAS: 9046-10-0 Polyoxypropylenediamine**

Oral DNEL 0.04 mg/kg bw/Tag (ArL)

Dermal DNEL 2.5 mg/kg bw/day (ArL)

**CAS: 9046-10-0 Polyoxypropylenediamine**

Oral DNEL 0.04 mg/kg bw/Tag (ArL)

Dermal DNEL 2.5 mg/kg bw/day (ArL)

**CAS: 90-72-2 2,4,6-Tri-(dimethylaminomethyl)phenol**

Inhalative DNEL 0.31 mg/m<sup>3</sup> (ArL)

**CAS: 15520-10-2 2-Methylpentamethylenediamine**

Dermal DNEL 1.5 mg/kg bw/day (ArL)

Inhalative DNEL 0.25 mg/m<sup>3</sup> (ArL)

0.5 mg/m<sup>3</sup> (Ark)

· **PNECs**

**CAS: 9046-10-0 Polyoxypropylenediamine**

PNEC 7.5 mg/l (Sewage Treatment Plant)

0.015 mg/l (Fresh water)

PNEC 0.0176 mg/kg dwt (Bod)

0.125 mg/kg dwt (Sediment)

0.132 mg/kg dwt (Fresh water sediment)

**CAS: 9046-10-0 Polyoxypropylenediamine**

PNEC 7.5 mg/l (Sewage Treatment Plant)

0.015 mg/l (Fresh water)

PNEC 0.0176 mg/kg dwt (Bod)

0.125 mg/kg dwt (Sediment)

0.132 mg/kg dwt (Fresh water sediment)

**CAS: 90-72-2 2,4,6-Tri-(dimethylaminomethyl)phenol**

PNEC 0.2 mg/l (Sewage Treatment Plant)

0.0084 mg/l (Mew)

0.084 mg/l (Freshwater)

**CAS: 15520-10-2 2-Methylpentamethylenediamine**

PNEC 0.042 mg/l (Mew)

0.42 mg/l (Freshwater)

(Contd. on page 6)



BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 17.04.2026

Version number 14 (replaces version 13)

Revision: 17.04.2026

**Trade name MC-DUR 1321 flex - Komponente B**

(Contd. of page 5)

**CAS: 25513-64-8 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine**

PNEC	72 mg/l (Sewage Treatment Plant)
	0.102 mg/l (Fresh water)
	0.01 mg/l (Mew)
PNEC	10 mg/kg dwt (Bod)
	0.062 mg/kg dwt (Sediment)
	0.622 mg/kg dwt (Fresh water sediment)

- **Additional information:** *The lists that were valid during the compilation were used as basis.*
- **8.2 Exposure controls**
- **Appropriate engineering controls** *No further data; see section 7.*
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures** *Keep away from food, drink and animal feed.  
Remove soiled, soaked clothing immediately.  
Wash hands before breaks and at the end of work.  
Avoid contact with eyes and skin.*
- **Breathing equipment:** *If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.*
- **Hand protection** *Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*
- **Material of gloves** *You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>  
For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.  
Nitrile rubber  
Recommended material thickness: ≥ 0.4 mm*
- **Penetration time of glove material** *The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.  
The following applies to all other gloves:  
The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.  
Nitrile rubber  
Material thickness: ≥ 0.40 mm  
Penetration time: ≥ 480 min*

(Contd. on page 7)



BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 17.04.2026

Version number 14 (replaces version 13)

Revision: 17.04.2026

**Trade name MC-DUR 1321 flex - Komponente B**

(Contd. of page 6)

· **Eye/face protection**

· **Body protection:**

*Butyl rubber:*

*Material thickness:  $\geq 0.5$  mm*

*Penetration time:  $\geq 480$  min*

*Tight-fitting safety goggles.*

*Safety goggles.*

*Protective clothing*

*Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.*

## SECTION 9: Physical and chemical properties

### · 9.1 Information on basic physical and chemical properties

#### · General Information

· **Physical state**

*Liquid*

· **Colour:**

*Yellowish*

· **Smell:**

*Amine-like*

· **Odour threshold:**

*Not determined*

· **Melting point/freezing point:**

*Not determined*

· **Boiling point or initial boiling point and boiling range**

*Not determined*

· **Flammability**

*Not applicable*

· **Lower and upper explosion limit**

· **Lower:**

*Not determined*

· **Upper:**

*Not determined*

· **Flash point:**

*Not applicable*

· **Decomposition temperature:**

*Not determined*

· **pH**

*Not determined*

· **Viscosity:**

· **Kinematic viscosity**

*Not determined*

· **dynamic at 20 °C:**

*220 mPas*

· **Solubility**

· **Water:**

*Partly miscible*

· **Partition coefficient n-octanol/water (log value)**

*Not determined*

· **Steam pressure:**

*Not determined*

· **Density and/or relative density**

· **Density at 20 °C**

*0.99 g/cm<sup>3</sup>*

· **Relative density**

*Not determined*

· **Vapour density**

*Not determined*

(Contd. on page 8)



BE SURE. BUILD SURE.

Page 8/14

## Safety data sheet according to UK REACH

Printing date 17.04.2026

Version number 14 (replaces version 13)

Revision: 17.04.2026

Trade name **MC-DUR 1321 flex - Komponente B**

(Contd. of page 7)

### · 9.2 Other information

#### · Appearance:

#### · Form:

Liquid

#### · Important information on protection of health and environment, and on safety.

#### · Self-inflammability:

Product is not selfigniting.

#### · Explosive properties:

Product is not explosive.

#### · Change in condition

#### · Evaporation rate

Not determined

#### · Information with regard to physical hazard classes

#### · Explosives

Void

#### · Flammable gases

Void

#### · Aerosols

Void

#### · Oxidising gases

Void

#### · Gases under pressure

Void

#### · Flammable liquids

Void

#### · Flammable solids

Void

#### · Self-reactive substances and mixtures

Void

#### · Pyrophoric liquids

Void

#### · Pyrophoric solids

Void

#### · Self-heating substances and mixtures

Void

#### · Substances and mixtures, which emit flammable gases in contact with water

Void

#### · Oxidising liquids

Void

#### · Oxidising solids

Void

#### · Organic peroxides

Void

#### · Corrosive to metals

Void

#### · Desensitised explosives

Void

## SECTION 10: Stability and reactivity

#### · 10.1 Reactivity

No further relevant information available.

#### · 10.2 Chemical stability

stable

#### · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

#### · 10.3 Possibility of hazardous reactions

No dangerous reactions known

#### · 10.4 Conditions to avoid

No further relevant information available.

#### · 10.5 Incompatible materials:

No further relevant information available.

#### · 10.6 Hazardous

#### decomposition products:

No dangerous decomposition products known

GB

(Contd. on page 9)



BE SURE. BUILD SURE.

**Safety data sheet  
according to UK REACH**

Printing date 17.04.2026

Version number 14 (replaces version 13)

Revision: 17.04.2026

**Trade name MC-DUR 1321 flex - Komponente B**

(Contd. of page 8)

**SECTION 11: Toxicological information**

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

**CAS: 9046-10-0 Polyoxypropylenediamine**

Oral	LD50	2855 mg/kg (Rat) 2885 mg/kg (rat)
Dermal	LD50	2980 mg/kg (Kan) 2980 mg/kg (rabbit)

**CAS: 9046-10-0 Polyoxypropylenediamine**

Oral	LD50	2855 mg/kg (Rat) 2885 mg/kg (rat)
Dermal	LD50	2980 mg/kg (Kan) 2980 mg/kg (rabbit)

**CAS: 93281-16-4 Phenol, reaction products with divinylbenzene**

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rat)

**CAS: 90-72-2 2,4,6-Tri-(dimethylaminomethyl)phenol**

Oral	LD50	mg/kg (rat)
	NOAEL	15 mg/kg (rat)

**CAS: 15520-10-2 2-Methylpentamethylenediamine**

Oral	LD50	1170 mg/kg (rat)
Dermal	LD50	1870 mg/kg (rabbit)
Inhalative	LC50/4 h	19.6 mg/l (rat)

**CAS: 25513-64-8 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine**

Oral	LD50	910 mg/kg (rat)
	NOAEL	10 mg/kg (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

GB

(Contd. on page 10)



BE SURE. BUILD SURE.

**Safety data sheet  
according to UK REACH**

Printing date 17.04.2026

Version number 14 (replaces version 13)

Revision: 17.04.2026

**Trade name MC-DUR 1321 flex - Komponente B**

(Contd. of page 9)

**SECTION 12: Ecological information**

**· 12.1 Toxicity**

**· Aquatic toxicity:**

**CAS: 9046-10-0 Polyoxypropylenediamine**

EC50/72h	15 mg/l (algae)
LC50/96h	>15 mg/l (fish)
EC50/48h	80 mg/l (daphnia)

**CAS: 9046-10-0 Polyoxypropylenediamine**

EC50/72h	15 mg/l (algae)
LC50/96h	>15 mg/l (fish)
EC50/48h	80 mg/l (daphnia)

**CAS: 90-72-2 2,4,6-Tri-(dimethylaminomethyl)phenol**

EC50/72h	84 mg/l (Desmodesmus subspicatus)
LC50/96h	175 mg/l (Cyp)
	718 mg/l (Daphnia magna)
NOEC	2 mg/l (BEL)
	6.25 mg/l (Desmodesmus subspicatus)

**CAS: 15520-10-2 2-Methylpentamethylenediamine**

EC50/72h	>100 mg/l (algae)
EC50	1825 mg/l (fish)
EC50/48h	19.8 mg/l (Daphnia magna)

**CAS: 25513-64-8 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine**

EC50/24h	31.5 mg/l (Daphnien)
EC50	89 mg/l (Pseudomonas putida)
LC50/48h	174 mg/l (Leucidus idus)
NOEC	10.9 mg/l (Danio rerio)
	16 mg/l (Pseudokirchneriella subcapitata)
	1.02 mg/l (Daphnia magna)
ErC50/72h	43.5 mg/l (Pseudokirchneriella subcapitata)

**· 12.2 Persistence and degradability**

No further relevant information available.

**· 12.3 Bioaccumulative potential**

No further relevant information available.

**· 12.4 Mobility in soil**

No further relevant information available.

**· 12.5 Results of PBT and vPvB assessment**

**· PBT:**

Not applicable

**· vPvB:**

Not applicable

**· 12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

(Contd. on page 11)



BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 17.04.2026

Version number 14 (replaces version 13)

Revision: 17.04.2026

**Trade name MC-DUR 1321 flex - Komponente B**

(Contd. of page 10)

- **12.7 Other adverse effects**
- **Remark:** Very toxic for fish
- **Additional ecological information:**
- **General notes:** Very toxic for aquatic organisms  
Must not reach sewage water or drainage ditch undiluted or unneutralised.  
Also poisonous for fish and plankton in water bodies.  
Danger to drinking water if even extremely small quantities leak into soil.

#### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.
- **Recommended cleaning agent:** Water, if necessary with cleaning agent.

#### SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN2735
- **14.2 UN proper shipping name**
- **ADR** AMINES, LIQUID, CORROSIVE, N.O.S. (Polyoxypropylenediamine), ENVIRONMENTALLY HAZARDOUS
- **IMDG** AMINES, LIQUID, CORROSIVE, N.O.S. (Polyoxypropylenediamine, alkylamine), MARINE POLLUTANT
- **IATA** AMINES, LIQUID, CORROSIVE, N.O.S. (Polyoxypropylenediamine)
- **14.3 Transport hazard class(es)**
- **ADR**
- **Class** 8 (C7) Corrosive substances.
- **Label** 8
- **IMDG, IATA**
- **Class** 8 Corrosive substances.
- **Label** 8
- **14.4 Packing group**
- **ADR, IMDG, IATA** II

(Contd. on page 12)



BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 17.04.2026

Version number 14 (replaces version 13)

Revision: 17.04.2026

**Trade name MC-DUR 1321 flex - Komponente B**

(Contd. of page 11)

**· 14.5 Environmental hazards:**

- **Marine pollutant:** Yes  
Symbol (fish and tree)
- **Special marking (ADR):** Symbol (fish and tree)

**· 14.6 Special precautions for user**

- **Warning:** Corrosive substances.
- **Kemler Number:** 80
- **EMS Number:** F-A, S-B
- **Segregation groups:** (SGG18) Alkalis
- **Stowage Category:** A
- **Segregation Code:** SG35 Stow "separated from" SGG1-acids

**· 14.7 Maritime transport in bulk according to IMO instruments**

Not applicable

**· Transport/Additional information:**

**· ADR**

- **Limited quantities (LQ):** 1L
- **Excepted quantities (EQ):** Code: E2  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 500 ml
- **Transport category:** 2
- **Tunnel restriction code:** E

**· IMDG**

- **Limited quantities (LQ):** 1L
- **Excepted quantities (EQ):** Code: E2  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 500 ml

**· UN "Model Regulation":**

UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (POLYOXYPROPYLENEDIAMINE), 8, II, ENVIRONMENTALLY HAZARDOUS

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

**· Regulated explosives precursors**

None of the ingredients is listed.

**· Regulated poisons**

None of the ingredients is listed.

**· Reportable explosives precursors**

None of the ingredients is listed.

(Contd. on page 13)



BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 17.04.2026

Version number 14 (replaces version 13)

Revision: 17.04.2026

**Trade name MC-DUR 1321 flex - Komponente B**

(Contd. of page 12)

**· Reportable poisons**

None of the ingredients is listed.

**· Directive 2012/18/EU**

**· Named dangerous substances - ANNEX I**

None of the ingredients is listed.

**· Seveso category**

E1 Hazardous to the Aquatic Environment

**· Qualifying quantity (tonnes) for the application of lower-tier requirements**

100 t

**· Qualifying quantity (tonnes) for the application of upper-tier requirements**

200 t

**· 15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

**· Relevant phrases**

H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H410 Very toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

**· Department issuing data specification sheet:**

Environment protection department.

**· Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation  
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
DNEL: Derived No-Effect Level (UK REACH)  
PNEC: Predicted No-Effect Concentration (UK REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 14)



BE SURE. BUILD SURE.

Page 14/14

## Safety data sheet according to UK REACH

Printing date 17.04.2026

Version number 14 (replaces version 13)

Revision: 17.04.2026

**Trade name MC-DUR 1321 flex - Komponente B**

(Contd. of page 13)

*vPvB: very Persistent and very Bioaccumulative*

*Acute Tox. 4: Acute toxicity – Category 4*

*Skin Corr. 1A: Skin corrosion/irritation – Category 1A*

*Skin Corr. 1B: Skin corrosion/irritation – Category 1B*

*Skin Corr. 1C: Skin corrosion/irritation – Category 1C*

*Skin Irrit. 2: Skin corrosion/irritation – Category 2*

*Eye Dam. 1: Serious eye damage/eye irritation – Category 1*

*Skin Sens. 1: Skin sensitisation – Category 1*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

*STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2*

*Asp. Tox. 1: Aspiration hazard – Category 1*

*Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1*

*Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

**\* Data compared to the  
previous version altered.**

GB