



BE SURE. BUILD SURE.

Page 1/12

Safety data sheet according to UK REACH

Printing date 06.03.2026

Version number 10 (replaces version 9)

Revision: 06.03.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name** **MC-DUR 1350 VK - Komponente A**

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Sector of Use** SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Application of the substance / the mixture**

Priming

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:** MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Siloring 8
CH-5606 Dintikon
Tel. +41 56 616 68 68
Fax +41 56 616 68 69

· **Informing department:** msds@mc-bauchemie.de

· **1.4 Emergency telephone number:**

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· **2.2 Label elements**

· **Labelling according to**

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**



GHS07 GHS09

· **Signal word**

Warning

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 06.03.2026

Version number 10 (replaces version 9)

Revision: 06.03.2026

Trade name MC-DUR 1350 VK - Komponente A

(Contd. of page 1)

- **Hazard-determining components of labelling:** 4,4'-Methylenediphenyldiglycidyl ether
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane
- **Hazard statements** H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements** P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves / eye protection / face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable
- **vPvB:** Not applicable

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Resin mixture with colouring agents.
Mixture consisting of the following components.

· **Dangerous components:**

CAS: 1675-54-3	4,4'-Methylenediphenyldiglycidyl ether Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	80-100%
CAS: 25322-69-4	Polypropylene glycol Acute Tox. 4, H302	<5%
CAS: 9003-36-5	Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥2.5-<5%
CAS: 108-32-7 EINECS: 203-572-1	Propylene carbonate Eye Irrit. 2, H319	<2.5%

(Contd. on page 3)



BE SURE. BUILD SURE.

Page 3/12

Safety data sheet according to UK REACH

Printing date 06.03.2026

Version number 10 (replaces version 9)

Revision: 06.03.2026

Trade name MC-DUR 1350 VK - Komponente A

· **Additional information**

For the wording of the listed hazard phrases refer to section 16.

(Contd. of page 2)

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

- **General information** Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.
- **After inhalation** Supply fresh air; seek medical advice if symptoms occur. If unconscious, place in recovery position and seek medical advice.
- **After skin contact** In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
- **After eye contact** Rinse opened eye for several minutes under running water. Call a doctor immediately
- **After swallowing** Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.

· **4.2 Most important symptoms and effects, both acute and delayed**

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained breathing apparatus.
- **Additional information** Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required
- **6.2 Environmental precautions:** Dilute with much water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections** See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

GB



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 06.03.2026

Version number 10 (replaces version 9)

Revision: 06.03.2026

Trade name MC-DUR 1350 VK - Komponente A

See Section 13 for information on disposal.

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Open and handle containers with care.

Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms), because the occupational exposure limit values (see chapter 8) could be exceeded. This must be avoided.

Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.

Store in cool, dry place in tightly closed containers.

· Information about protection against explosions and fires:

Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

· Requirements to be met by storerooms and containers:

No special requirements.

· Information about storage in one common storage facility:

Store away from foodstuffs.

· Further information about storage conditions:

None.

· Storage class

10

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· Additional information:

The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls

No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures

Keep away from food, drink and animal feed.
Remove soiled, soaked clothing immediately.

(Contd. on page 5)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 06.03.2026

Version number 10 (replaces version 9)

Revision: 06.03.2026

Trade name MC-DUR 1350 VK - Komponente A

(Contd. of page 4)

· **Breathing equipment:**

Wash hands before breaks and at the end of work.
Avoid contact with eyes and skin.

If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.

· **Hand protection**

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>

For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material".

The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product

is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.

Nitrile rubber

Recommended material thickness: ≥ 0.4 mm

· **Penetration time of glove material**

The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm

Penetration time: ≥ 480 min

Butyl rubber:

Material thickness: ≥ 0.5 mm

Penetration time: ≥ 480 min

· **Eye/face protection**

Tight-fitting safety goggles.

Safety goggles.

· **Body protection:**

Protective clothing

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

GB

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 06.03.2026

Version number 10 (replaces version 9)

Revision: 06.03.2026

Trade name MC-DUR 1350 VK - Komponente A

(Contd. of page 5)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

· Physical state	Liquid
· Colour:	Colourless
· Smell:	Characteristic
· Odour threshold:	Not determined
· Melting point/freezing point:	Not determined
· Boiling point or initial boiling point and boiling range	> 320 °C (CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether)
· Flammability	Not applicable
· Lower and upper explosion limit	
· Lower:	Not determined
· Upper:	Not determined
· Flash point:	>249 °C
· Auto-ignition temperature:	455 °C (CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether)
· Decomposition temperature:	Not determined
· pH	Not determined
· Viscosity:	
· Kinematic viscosity	Not determined
· dynamic at 20 °C:	4300 mPas
· Solubility	
· Water:	Not miscible or difficult to mix
· Partition coefficient n-octanol/water (log value)	Not determined
· Steam pressure at 25 °C:	0 hPa (CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether)
· Density and/or relative density	
· Density at 20 °C	1.15 g/cm ³
· Relative density	Not determined
· Vapour density	Not determined

9.2 Other information

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.
· Change in condition	
· Evaporation rate	Not determined

Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void

(Contd. on page 7)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 06.03.2026

Version number 10 (replaces version 9)

Revision: 06.03.2026

Trade name MC-DUR 1350 VK - Komponente A

(Contd. of page 6)

· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability** stable
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Possible in traces.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether

Oral	LD50	11400 mg/kg (rat)
Dermal	LD50	23000 mg/kg (rabbit)
		>2000 mg/kg (rat)

CAS: 25322-69-4 Polypropylene glycol

Oral	LD50	1000-<2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

(Contd. on page 8)



BE SURE. BUILD SURE.

Page 8/12

Safety data sheet according to UK REACH

Printing date 06.03.2026

Version number 10 (replaces version 9)

Revision: 06.03.2026

Trade name MC-DUR 1350 VK - Komponente A

(Contd. of page 7)

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl) oxirane

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

CAS: 108-32-7 Propylene carbonate

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

CAS: 78-93-3	butanone
--------------	----------

List II

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether

LC50/72h	>11 mg/l (algae)
IC50	>42.6 mg/l (Bak)
LC50/96h	2 mg/l (Oncorhynchus mykiss)
	1.3 mg/l (fish)
EC50/48h	2.1 mg/l (daphnia)
	1.8 mg/l (Daphnia magna)
ErC50/72h	11 mg/l (Selenastrum capricornutum)

CAS: 25322-69-4 Polypropylene glycol

LC50/48h	>100 mg/l (Leucidus idus)
EC50/48h	>100 mg/l (Daphnia magna)
EC0	>100 mg/l (Desmodesmus subspicatus)

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl) oxirane

LC50/96h	>100 mg/l (Daphnia magna)
EC50/96h	>100 mg/l (Leucidus idus)

(Contd. on page 9)

GB



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 06.03.2026

Version number 10 (replaces version 9)

Revision: 06.03.2026

Trade name MC-DUR 1350 VK - Komponente A

(Contd. of page 8)

- **12.2 Persistence and degradability** *No further relevant information available.*
- **12.3 Bioaccumulative potential** *No further relevant information available.*
- **12.4 Mobility in soil** *No further relevant information available.*
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** *Not applicable*
- **vPvB:** *Not applicable*
- **12.6 Endocrine disrupting properties** *For information on endocrine disrupting properties see section 11.*
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** *Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.*

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** *Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- **Uncleaned packagings:**
- **Recommendation:** *Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.*
- **Recommended cleaning agent:** *Water, if necessary with cleaning agent.*

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** *UN3082*
- **14.2 UN proper shipping name**
- **ADR, IATA** *ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxide resin)*
- **IMDG** *ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxide resin), MARINE POLLUTANT*
- **14.3 Transport hazard class(es)**
- **ADR**
- **Class** *9 (M6) Miscellaneous dangerous substances and articles.*
- **Label** *9*

(Contd. on page 10)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 06.03.2026

Version number 10 (replaces version 9)

Revision: 06.03.2026

Trade name MC-DUR 1350 VK - Komponente A

(Contd. of page 9)

· IMDG, IATA · Class	9 Miscellaneous dangerous substances and articles.
· Label	9
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	Product contains environmentally hazardous substances: Epoxide resin Yes
· Special marking (ADR): · Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user · Kemler Number: · EMS Number: · Stowage Category	Warning: Miscellaneous dangerous substances and articles. 90 F-A,S-F A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category · Tunnel restriction code · Remarks:	3 (-) 1 kg Gebinde: Begrenzte Mengen
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE RESIN), 9, III

GB

(Contd. on page 11)



BE SURE. BUILD SURE.

**Safety data sheet
according to UK REACH**

Printing date 06.03.2026

Version number 10 (replaces version 9)

Revision: 06.03.2026

Trade name MC-DUR 1350 VK - Komponente A

(Contd. of page 10)

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I**

None of the ingredients is listed.

· **Seveso category**

E2 Hazardous to the Aquatic Environment

· **Qualifying quantity (tonnes) for the application of lower-tier requirements**

200 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements**

500 t

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

· **Relevant phrases**

H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

· **Department issuing data specification sheet:**

Environment protection department.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

(Contd. on page 12)



BE SURE. BUILD SURE.

Page 12/12

Safety data sheet according to UK REACH

Printing date 06.03.2026

Version number 10 (replaces version 9)

Revision: 06.03.2026

Trade name MC-DUR 1350 VK - Komponente A

(Contd. of page 11)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· * **Data compared to the
previous version altered.**

GB