



BE SURE. BUILD SURE.

Page 1/12

## Safety data sheet according to UK REACH

Printing date 06.03.2026

Version number 9 (replaces version 8)

Revision: 06.03.2026

### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· **1.1 Product identifier**

· **Trade name** **MC-DUR 1350 VK - Komponente B**

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Sector of Use** SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Application of the substance  
/ the mixture**

Priming

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:** MC-Bauchemie Müller GmbH & Co. KG  
Am Kruppwald 1-8  
D-46238 Bottrop  
Tel.: +49(0)2041-101-0  
Fax.: +49(0)2041-101-400  
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG  
Siloring 8  
CH-5606 Dintikon  
Tel. +41 56 616 68 68  
Fax +41 56 616 68 69

· **Informing department:** msds@mc-bauchemie.de

· **1.4 Emergency telephone  
number:**

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

### SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Acute Tox. 4 H302 Harmful if swallowed.

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

· **2.2 Label elements**

· **Labelling according to**

**Regulation (EC) No 1272/2008** The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**



GHS05 GHS07

· **Signal word**

Danger

· **Hazard-determining**

**components of labelling:** benzyl alcohol

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

**Safety data sheet  
according to UK REACH**

Printing date 06.03.2026

Version number 9 (replaces version 8)

Revision: 06.03.2026

**Trade name MC-DUR 1350 VK - Komponente B**

(Contd. of page 1)

- **Hazard statements**  
Isophoron Diamine  
Polymer with amino-functional groups  
2,4,6-Tri-(dimethylaminomethyl)phenol  
H302 Harmful if swallowed.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.
- **Precautionary statements**  
P260 Do not breathe dusts or mists.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER/doctor.  
P321 Specific treatment (see on this label).  
P362+P364 Take off contaminated clothing and wash it before reuse.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable
- **vPvB:** Not applicable

**SECTION 3: Composition/information on ingredients**

- **3.2 Mixtures**
- **Description:** Binding agent with colouring agents.  
Mixture consisting of the following components.

· **Dangerous components:**

CAS: 100-51-6 EINECS: 202-859-9 Reg.nr.: 01-2119492630-38	benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1B, H317 ATE: LD50 oral: 1200 mg/kg	30-60%
CAS: 2855-13-2	Isophoron Diamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317 ATE: LD50 oral: 1030 mg/kg	10-30%
CAS: 25322-69-4	Polypropylene glycol Acute Tox. 4, H302	30%
EC number: 949-140-2	Polymer with amino-functional groups Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317	≥3-<10%
CAS: 108-32-7 EINECS: 203-572-1	Propylene carbonate Eye Irrit. 2, H319	<10%
CAS: 90-72-2 EINECS: 202-013-9 Reg.nr.: 2119560597-27	2,4,6-Tri-(dimethylaminomethyl)phenol Skin Corr. 1C, H314; Eye Dam. 1, H318; Acute Tox. 4, H302	≥3-<5%

(Contd. on page 3)



BE SURE. BUILD SURE.

Page 3/12

## Safety data sheet according to UK REACH

Printing date 06.03.2026

Version number 9 (replaces version 8)

Revision: 06.03.2026

**Trade name MC-DUR 1350 VK - Komponente B**

(Contd. of page 2)

CAS: 15520-10-2  
EINECS: 239-556-6

2-Methylpentamethylenediamine  
Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4,  
H312; Acute Tox. 4, H332; STOT SE 3, H335

≥1-<5%

· **Additional information**

For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

· **4.1 Description of first aid measures**

- **After inhalation** Supply fresh air; consult doctor in case of symptoms.
- **After skin contact** The product is not skin irritating.
- **After eye contact** Rinse opened eye for several minutes under running water. Then consult a doctor.

### SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

- **Suitable extinguishing agents** CO<sub>2</sub>, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

· **5.2 Special hazards arising from the substance or mixture**

No further relevant information available.

· **5.3 Advice for firefighters**

· **Protective equipment:**

No special measures required.

### SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Not required

· **6.2 Environmental precautions:**

Dilute with much water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling  
See Section 8 for information on personal protection equipment.  
See Section 13 for information on disposal.

### SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.  
Open and handle container with care.

(Contd. on page 4)

GB



BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 06.03.2026

Version number 9 (replaces version 8)

Revision: 06.03.2026

**Trade name MC-DUR 1350 VK - Komponente B**

(Contd. of page 3)

Store in cool, dry place in tightly closed containers.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage**

· **Further information about storage conditions:**

Keep container tightly closed in a well-ventilated place.

· **Storage class**

8A

### SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Components with critical values that require**

**monitoring at the workplace:** The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **DNELs**

**CAS: 100-51-6 benzyl alcohol**

Oral	DNEL	4 mg/kg bw/Tag (ArL) 20 mg/kg bw/Tag (Ark)
Dermal	DNEL	8 mg/kg bw/day (ArL) 40 mg/kg bw/day (Ark)
Inhalative	DNEL	22 mg/m <sup>3</sup> (ArL) 110 mg/m <sup>3</sup> (Ark)

**CAS: 2855-13-2 Isophoron Diamine**

Oral	DNEL	0.526 mg/kg bw/Tag (ArL)
Inhalative	DNEL	20.1 mg/m <sup>3</sup> (ArL)

**CAS: 90-72-2 2,4,6-Tri-(dimethylaminomethyl)phenol**

Inhalative	DNEL	0.31 mg/m <sup>3</sup> (ArL)
------------	------	------------------------------

**CAS: 15520-10-2 2-Methylpentamethylenediamine**

Dermal	DNEL	1.5 mg/kg bw/day (ArL)
Inhalative	DNEL	0.25 mg/m <sup>3</sup> (ArL) 0.5 mg/m <sup>3</sup> (Ark)

· **PNECs**

**CAS: 100-51-6 benzyl alcohol**

PNEC	0.527 mg/l (Marine water sediment) 0.1 mg/l (Mew) 1 mg/l (Fresh water sediment)
PNEC	0.456 mg/kg dwt (Bod) 5.27 mg/kg dwt (Fresh water sediment)

**CAS: 2855-13-2 Isophoron Diamine**

PNEC	0.006 mg/l (Mew) 0.06 mg/l (Freshwater)
------	--

(Contd. on page 5)



BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 06.03.2026

Version number 9 (replaces version 8)

Revision: 06.03.2026

**Trade name MC-DUR 1350 VK - Komponente B**

(Contd. of page 4)

PNEC	0.578 mg/kg dwt (Sediment) 5.784 mg/kg dwt (Fresh water sediment)
<b>CAS: 90-72-2 2,4,6-Tri-(dimethylaminomethyl)phenol</b>	
PNEC	0.2 mg/l (Sewage Treatment Plant) 0.0084 mg/l (Mew) 0.084 mg/l (Freshwater)
<b>CAS: 15520-10-2 2-Methylpentamethylenediamine</b>	
PNEC	0.042 mg/l (Mew) 0.42 mg/l (Freshwater)

- **Additional information:** The lists that were valid during the compilation were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures**
  - Keep away from foodstuffs, beverages and food.
  - Instantly remove any soiled and impregnated garments.
  - Wash hands during breaks and at the end of the work.
  - Avoid contact with the skin.
  - Avoid contact with the eyes and skin.
- **Breathing equipment:** In case of brief exposure or low pollution or when application is performed at confined area with adequate mechanical ventilation meeting local authority requirements, use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.
- **Hand protection** Not required
- **Material of gloves** -
- **Penetration time of glove material** -
- **Eye/face protection** Not required

## SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Physical state** Liquid
- **Colour:** Yellow
- **Smell:** Amine-like
- **Odour threshold:** Not determined
- **Melting point/freezing point:** Not determined
- **Boiling point or initial boiling point and boiling range** >200 °C (CAS: 25322-69-4 Polypropylene glycol)
- **Flammability** Not applicable

(Contd. on page 6)



BE SURE. BUILD SURE.

Page 6/12

## Safety data sheet according to UK REACH

Printing date 06.03.2026

Version number 9 (replaces version 8)

Revision: 06.03.2026

Trade name MC-DUR 1350 VK - Komponente B

(Contd. of page 5)

· Lower and upper explosion limit	
· Lower:	1.3 Vol %
· Upper:	13 Vol %
· Flash point:	82 °C
· Auto-ignition temperature:	380 °C (CAS: 2855-13-2 Isophoron Diamine)
· Decomposition temperature:	Not determined
· pH	Not determined
· Viscosity:	
· Kinematic viscosity	Not determined
· dynamic at 20 °C:	170 mPas
· Solubility	
· Water:	Not miscible or difficult to mix
· Partition coefficient n-octanol/water (log value)	Not determined
· Steam pressure at 20 °C:	0.2 hPa (CAS: 100-51-6 Benzyl alcohol)
· Density and/or relative density	
· Density at 20 °C	1.02 g/cm <sup>3</sup>
· Relative density	Not determined
· Vapour density	Not determined

### · 9.2 Other information

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.
· Change in condition	
· Evaporation rate	Not determined

### · Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void

(Contd. on page 7)

GB



BE SURE. BUILD SURE.

**Safety data sheet  
according to UK REACH**

Printing date 06.03.2026

Version number 9 (replaces version 8)

Revision: 06.03.2026

**Trade name MC-DUR 1350 VK - Komponente B**

(Contd. of page 6)

· **Desensitised explosives**

Void

**SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability** stable
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

**SECTION 11: Toxicological information**

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if swallowed.

· **LD/LC50 values that are relevant for classification:**

**CAS: 100-51-6 benzyl alcohol**

Oral	LD50	1200 mg/kg (ATE) 1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse) 200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)

**CAS: 2855-13-2 Isophoron Diamine**

Oral	LD50	1030 mg/kg (ATE) 1030 mg/kg (rat)
	NOAEL	250 mg/kg (rat)
Dermal	LD50	1840 mg/kg (rabbit) >2000 mg/kg (rat)
		1840 mg/kg (rabbit)

**CAS: 25322-69-4 Polypropylene glycol**

Oral	LD50	1000-<2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

**CAS: 108-32-7 Propylene carbonate**

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

(Contd. on page 8)



BE SURE. BUILD SURE.

**Safety data sheet  
according to UK REACH**

Printing date 06.03.2026

Version number 9 (replaces version 8)

Revision: 06.03.2026

**Trade name MC-DUR 1350 VK - Komponente B**

(Contd. of page 7)

**CAS: 90-72-2 2,4,6-Tri-(dimethylaminomethyl)phenol**

Oral	LD50	mg/kg (rat)
	NOAEL	15 mg/kg (rat)

**CAS: 15520-10-2 2-Methylpentamethylenediamine**

Oral	LD50	1170 mg/kg (rat)
Dermal	LD50	1870 mg/kg (rabbit)
Inhalative	LC50/4 h	19.6 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

CAS: 78-93-3 butanone

List II

**SECTION 12: Ecological information**

· **12.1 Toxicity**

· **Aquatic toxicity:**

**CAS: 100-51-6 benzyl alcohol**

IC50/72h	700 mg/l (algae)
LC50/96h	460 mg/l ( <i>Pimephales promelas</i> )
	10 mg/l ( <i>Lepomis macrochirus</i> )

**CAS: 2855-13-2 Isophoron Diamine**

LC50/96h	110 mg/l (fish)
	110 mg/l ( <i>Leucidus idus</i> )
EC50	1120 mg/l ( <i>Pseudomonas putida</i> )
EC50/48h	23 mg/l ( <i>daphnia</i> )
	23 mg/l ( <i>Daphnia magna</i> )
NOEC	1.5 mg/l ( <i>Desmodesmus subspicatus</i> )
	3 mg/l ( <i>Daphnia magna</i> )
ErC50/72h	>50 mg/l ( <i>Desmodesmus subspicatus</i> )
	>50 mg/l (algae)

**CAS: 25322-69-4 Polypropylene glycol**

LC50/48h	>100 mg/l ( <i>Leucidus idus</i> )
EC50/48h	>100 mg/l ( <i>Daphnia magna</i> )
EC0	>100 mg/l ( <i>Desmodesmus subspicatus</i> )

**CAS: 90-72-2 2,4,6-Tri-(dimethylaminomethyl)phenol**

EC50/72h	84 mg/l ( <i>Desmodesmus subspicatus</i> )
----------	--

(Contd. on page 9)



BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 06.03.2026

Version number 9 (replaces version 8)

Revision: 06.03.2026

**Trade name MC-DUR 1350 VK - Komponente B**

(Contd. of page 8)

LC50/96h	175 mg/l (Cyp) 718 mg/l (Daphnia magna)
NOEC	2 mg/l (BEL) 6.25 mg/l (Desmodesmus subspicatus)
<b>CAS: 15520-10-2 2-Methylpentamethylenediamine</b>	
EC50/72h	>100 mg/l (algae)
EC50	1825 mg/l (fish)
EC50/48h	19.8 mg/l (Daphnia magna)

- **12.2 Persistence and degradability** *No further relevant information available.*
- **12.3 Bioaccumulative potential** *No further relevant information available.*
- **12.4 Mobility in soil** *No further relevant information available.*
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** *Not applicable*
- **vPvB:** *Not applicable*
- **12.6 Endocrine disrupting properties** *For information on endocrine disrupting properties see section 11.*
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** *Do not allow product to reach ground water, water bodies or sewage system.  
Danger to drinking water if even small quantities leak into soil.*

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** *Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- **Uncleaned packagings:**
- **Recommendation:** *Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.*
- **Recommended cleaning agent:** *Water, if necessary with cleaning agent.*

### SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** *UN2735*

(Contd. on page 10)



BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 06.03.2026

Version number 9 (replaces version 8)

Revision: 06.03.2026

**Trade name MC-DUR 1350 VK - Komponente B**

(Contd. of page 9)

<ul style="list-style-type: none"> <li>· <b>14.2 UN proper shipping name</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>	<p>AMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONEDIAMINE, 2,4,6-Tri-(dimethylaminomethyl)phenol)</p>
<ul style="list-style-type: none"> <li>· <b>14.3 Transport hazard class(es)</b></li> <li>· <b>ADR</b></li> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>	<p>8 (C7) Corrosive substances. 8</p>
<ul style="list-style-type: none"> <li>· <b>IMDG, IATA</b></li> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>	<p>8 Corrosive substances. 8</p>
<ul style="list-style-type: none"> <li>· <b>14.4 Packing group</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>	<p>II</p>
<ul style="list-style-type: none"> <li>· <b>14.5 Environmental hazards:</b></li> <li>· <b>Marine pollutant:</b></li> </ul>	<p>No</p>
<ul style="list-style-type: none"> <li>· <b>14.6 Special precautions for user</b></li> <li>· <b>Kemler Number:</b></li> <li>· <b>EMS Number:</b></li> <li>· <b>Segregation groups</b></li> <li>· <b>Stowage Category</b></li> <li>· <b>Segregation Code</b></li> </ul>	<p>Warning: Corrosive substances. 80 F-A,S-B (SGG18) Alkalis A SG35 Stow "separated from" SGG1-acids</p>
<ul style="list-style-type: none"> <li>· <b>14.7 Maritime transport in bulk according to IMO instruments</b></li> </ul>	<p>Not applicable</p>
<ul style="list-style-type: none"> <li>· <b>Transport/Additional information:</b></li> <li>· <b>ADR</b></li> <li>· <b>Limited quantities (LQ)</b></li> <li>· <b>Excepted quantities (EQ)</b></li> <li>· <b>Transport category</b></li> <li>· <b>Tunnel restriction code</b></li> </ul>	<p>1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml 2 E</p>
<ul style="list-style-type: none"> <li>· <b>IMDG</b></li> <li>· <b>Limited quantities (LQ)</b></li> <li>· <b>Excepted quantities (EQ)</b></li> </ul>	<p>1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml</p>
<ul style="list-style-type: none"> <li>· <b>UN "Model Regulation":</b></li> </ul>	<p>UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONEDIAMINE, 2,4,6-TRI-(DIMETHYLAMINOMETHYL)PHENOL), 8, II</p>

GB

(Contd. on page 11)



BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 06.03.2026

Version number 9 (replaces version 8)

Revision: 06.03.2026

**Trade name MC-DUR 1350 VK - Komponente B**

(Contd. of page 10)

#### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

· **Relevant phrases**

H302 Harmful if swallowed.  
 H312 Harmful in contact with skin.  
 H314 Causes severe skin burns and eye damage.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.

· **Department issuing data specification sheet:**

Environment protection department.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 ICAO: International Civil Aviation Organisation  
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 DNEL: Derived No-Effect Level (UK REACH)  
 PNEC: Predicted No-Effect Concentration (UK REACH)  
 LC50: Lethal concentration, 50 percent

(Contd. on page 12)



BE SURE. BUILD SURE.

Page 12/12

## Safety data sheet according to UK REACH

Printing date 06.03.2026

Version number 9 (replaces version 8)

Revision: 06.03.2026

**Trade name MC-DUR 1350 VK - Komponente B**

(Contd. of page 11)

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*ATE: Acute toxicity estimate values*

*Acute Tox. 4: Acute toxicity – Category 4*

*Skin Corr. 1A: Skin corrosion/irritation – Category 1A*

*Skin Corr. 1B: Skin corrosion/irritation – Category 1B*

*Skin Corr. 1C: Skin corrosion/irritation – Category 1C*

*Skin Irrit. 2: Skin corrosion/irritation – Category 2*

*Eye Dam. 1: Serious eye damage/eye irritation – Category 1*

*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*

*Skin Sens. 1: Skin sensitisation – Category 1*

*Skin Sens. 1A: Skin sensitisation – Category 1A*

*Skin Sens. 1B: Skin sensitisation – Category 1B*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

**\* Data compared to the  
previous version altered.**

GB