

MC-DUR 2060 UV flow

Reference number of the Declaration of Performance: IN5463732

1. Unique ID code of the product type	MC-DUR 2060 UV flow
2. Application(s)	coating Protection against ingress (1.3) Moisture control (2.2) Physical resistance (5.1)
3. Manufacturer	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany
4. Authorized representative	-
5. System of AVCP	System 2+ System 4
6. Harmonised standard	EN 1504-2: 2004
7. Notified body	Institut für Massivbau und Baustofftechnologie Universität Karlsruhe (TH) ID code 0754

8. Declared performances


Essential characteristic	Performance	harmonised technical specification
Wear resistance	≤ 3000 mg (H22/1000/1000)	EN 1504-2: 2004
CO ₂ permeability	Sd > 50 m	
Water vapour permeability	class II $5 \text{ m} \leq S_D \leq 50 \text{ m}$	
Capillary water absorption	$< 0.1 \text{ kg/m}^2 \cdot \text{h}^{0.5}$	
Crack-bridging capacity	A3	
Impact strength	class I: $\geq 4 \text{ Nm}$	
Tear-off test to determine adhesive strength	≥ 1.0 (0.7) N/mm ²	
Fire behaviour	B _{fl} -s1	

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

John van Diemen
Head of Research & Development and Quality

Bottrop, 24.01.2026
(place and date of issue)



(signature)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.