



BE SURE. BUILD SURE.

Page 1/13

Safety data sheet according to UK REACH

Printing date 03.10.2025

Version number 35 (replaces version 34)

Revision: 03.10.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name**

MC-DUR ChemProtect AS - Komponente A

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Sector of Use**

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Product category**

PC9a Coatings and paints, thinners, paint removers

· **Application of the substance / the mixture**

Epoxy coating

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

· **Informing department:**

msds@mc-bauchemie.de

· **1.4 Emergency telephone number:**

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT RE 2 H373 May cause damage to the lung through prolonged or repeated exposure.
Route of exposure: Inhalation.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· **2.2 Label elements**

· **Labelling according to**

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**



GHS07 GHS08 GHS09

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

Page 2/13

Safety data sheet according to UK REACH

Printing date 03.10.2025

Version number 35 (replaces version 34)

Revision: 03.10.2025

Trade name MC-DUR ChemProtect AS - Komponente A

(Contd. of page 1)

- **Signal word** Warning
- **Hazard-determining components of labelling:**
 - Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] bis(oxirane) and 2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane
 - Quartz sand
 - 4,4'-Methylenediphenyldiglycidyl ether
 - Poly(oxy-1,4-butanediyl), α -(2-oxiranylmethyl)- ω -(2-oxiranylmethoxy)-
 - decarboxylating cashew nut shell liquid
 - Polymer with epoxy-functional groups
 - Polypropylenglycole-diepoxydresin
 - Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives
- **Hazard statements**
 - H315 Causes skin irritation.
 - H319 Causes serious eye irritation.
 - H317 May cause an allergic skin reaction.
 - H373 May cause damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.
 - H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements**
 - P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 - P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 - P273 Avoid release to the environment.
 - P280 Wear protective gloves / eye protection / face protection.
 - P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - P332+P313 If skin irritation occurs: Get medical advice/attention.
- **Additional information:** EUH205 Contains epoxy constituents. May produce an allergic reaction.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Resin mixture with colouring agents.
Mixture consisting of the following components.

(Contd. on page 3)

GB



BE SURE. BUILD SURE.

Page 3/13

Safety data sheet according to UK REACH

Printing date 03.10.2025

Version number 35 (replaces version 34)

Revision: 03.10.2025

Trade name MC-DUR ChemProtect AS - Komponente A

(Contd. of page 2)

· Dangerous components:

CAS: 9003-36-5	Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	30-60%
CAS: 1675-54-3	4,4'-Methylenediphenyldiglycidyl ether Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥10-<25%
CAS: 14808-60-7 EINECS: 238-878-4	Quartz sand STOT RE 1, H372	<10%
CAS: 26951-52-0	Poly(oxy-1,4-butanediyl), α-(2-oxiranylmethyl)-ω-(2-oxiranylmethoxy)- Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥1-<10%
CAS: 8007-24-7 EINECS: 232-355-4	decarboxylating cashew nut shell liquid Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥1-<2.5%
EC number: 953-811-5	Polymer with epoxy-functional groups Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥1-<1.5%
CAS: 26142-30-3	Polypropylenglycole-diepoxydresin Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1B, H317, EUH205	≥0.1-<1%
CAS: 68609-97-2 EINECS: 271-846-8	Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives Skin Irrit. 2, H315; Skin Sens. 1, H317, EUH205	≥0.1-<1%

· Additional information

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information

Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.

· After inhalation

Supply fresh air; seek medical advice if symptoms occur.

· After skin contact

If unconscious, place in recovery position and seek medical advice. In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.

· After eye contact

Rinse opened eye for several minutes under running water.

· After swallowing

Call a doctor immediately. Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.

(Contd. on page 4)

GB



BE SURE. BUILD SURE.

Page 4/13

Safety data sheet according to UK REACH

Printing date 03.10.2025

Version number 35 (replaces version 34)

Revision: 03.10.2025

Trade name MC-DUR ChemProtect AS - Komponente A

(Contd. of page 3)

- **4.2 Most important symptoms and effects, both acute and delayed**

Advice for the doctor: *Elementary aid, decontamination, symptomatic treatment.*

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** *Use fire fighting measures that suit the environment.*
- **5.2 Special hazards arising from the substance or mixture** *No further relevant information available.*
- **5.3 Advice for firefighters**
- **Protective equipment:** *No special measures required.*

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** *Not required.*
- **6.2 Environmental precautions:** *Dilute with much water.*
- **6.3 Methods and material for containment and cleaning up:** *Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).*
- **6.4 Reference to other sections** *See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.*

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** *Open and handle containers with care.
Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms), because the occupational exposure limit values (see chapter 8) could be exceeded. This must be avoided.
Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.*

(Contd. on page 5)

GB



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 03.10.2025

Version number 35 (replaces version 34)

Revision: 03.10.2025

Trade name MC-DUR ChemProtect AS - Komponente A

(Contd. of page 4)

- **Information about protection against explosions and fires:** *Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.*
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** *No special requirements.*
- **Further information about storage conditions:** *None.*
- **Storage class** *10*

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:** *The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.*

· **DNELs**

CAS: 68609-97-2 Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives

Dermal	DNEL	0.75 mg/kg bw/day (ArL)
Inhalative	DNEL	0.49 mg/m ³ (ArL)

· **PNECs**

CAS: 68609-97-2 Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives

PNEC	0.00072 mg/l (Mew)
	0.0072 mg/l (Freshwater)
PNEC	80.12 mg/kg dwt (Bod)
	6.677 mg/kg dwt (Sediment)
	66.77 mg/kg dwt (Fresh water sediment)

- **Additional information:** *The lists that were valid during the compilation were used as basis.*

· **8.2 Exposure controls**

- **Appropriate engineering controls** *No further data; see section 7.*
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures** *Keep away from food, drink and animal feed.
Remove soiled, soaked clothing immediately.
Wash hands before breaks and at the end of work.
Avoid contact with eyes and skin.*

- **Breathing equipment:** *If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe*

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 03.10.2025

Version number 35 (replaces version 34)

Revision: 03.10.2025

Trade name MC-DUR ChemProtect AS - Komponente A

(Contd. of page 5)

· Hand protection

wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.

· Material of gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>

For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.

Nitrile rubber

Recommended material thickness: ≥ 0.4 mm

· Penetration time of glove material

The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm

Penetration time: ≥ 480 min

Butyl rubber:

Material thickness: ≥ 0.5 mm

Penetration time: ≥ 480 min

· Eye/face protection

Tight-fitting safety goggles.

Safety goggles.

· Body protection:

Protective clothing

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state

Liquid

· Colour:

Pigmented

· Smell:

Product specific

(Contd. on page 7)



BE SURE. BUILD SURE.

Page 7/13

Safety data sheet according to UK REACH

Printing date 03.10.2025

Version number 35 (replaces version 34)

Revision: 03.10.2025

Trade name MC-DUR ChemProtect AS - Komponente A

(Contd. of page 6)

· Odour threshold:	Not determined.
· Melting point/freezing point:	Not determined
· Boiling point or initial boiling point and boiling range	> 320 °C (CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether)
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	121 °C
· Auto-ignition temperature:	455 °C (CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether)
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· dynamic at 20 °C:	9560 mPas
· Solubility	
· Water:	Fully miscible
· Partition coefficient n-octanol/water (log value)	Not determined.
· Steam pressure at 20 °C:	0.8 hPa (Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] dioxirane)
· Density and/or relative density	
· Density at 20 °C	1.38 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

9.2 Other information

· Appearance:	
· Form:	Liquid
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.
· Change in condition	
· Evaporation rate	Not determined.

Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void

(Contd. on page 8)

GB



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 03.10.2025

Version number 35 (replaces version 34)

Revision: 03.10.2025

Trade name MC-DUR ChemProtect AS - Komponente A

(Contd. of page 7)

· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
· 10.2 Chemical stability	stable
· Thermal decomposition / conditions to be avoided:	No decomposition if used according to specifications.
· 10.3 Possibility of hazardous reactions	No dangerous reactions known
· 10.4 Conditions to avoid	No further relevant information available.
· 10.5 Incompatible materials:	No further relevant information available.
· 10.6 Hazardous decomposition products:	No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl} oxirane

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether

Oral	LD50	11400 mg/kg (rat)
Dermal	LD50	23000 mg/kg (rabbit)
		>2000 mg/kg (rat)

(Contd. on page 9)



BE SURE. BUILD SURE.

Page 9/13

**Safety data sheet
according to UK REACH**

Printing date 03.10.2025

Version number 35 (replaces version 34)

Revision: 03.10.2025

Trade name MC-DUR ChemProtect AS - Komponente A

(Contd. of page 8)

CAS: 26142-30-3 Polypropylenglycole-diepoxidresin

Oral LD50 >2000 mg/kg (rat)

Dermal LD50 >2000 mg/kg (rat)

CAS: 68609-97-2 Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives

Oral LD50 17100 mg/kg (rat)

· **Primary irritant effect:**· **Skin corrosion/irritation** Causes skin irritation.· **Serious eye damage/irritation** Causes serious eye irritation.· **Respiratory or skin****sensitisation**

May cause an allergic skin reaction.

· **STOT-repeated exposure**

May cause damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

· **11.2 Information on other hazards**· **Endocrine disrupting properties**

CAS: 128-37-0 2,6-Di-tert-butyl-p-cresol

List II

CAS: 556-67-2 octamethylcyclotetrasiloxane

List II

SECTION 12: Ecological information· **12.1 Toxicity**· **Aquatic toxicity:****CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl} oxirane**

LC50/96h >100 mg/l (Daphnia magna)

EC50/96h >100 mg/l (Leucidus idus)

CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether

LC50/72h >11 mg/l (algae)

IC50 >42.6 mg/l (Bak)

LC50/96h 2 mg/l (Oncorhynchus mykiss)

1.3 mg/l (fish)

EC50/48h 2.1 mg/l (daphnia)

1.8 mg/l (Daphnia magna)

ErC50/72h 11 mg/l (Selenastrum capricornutum)

CAS: 26142-30-3 Polypropylenglycole-diepoxidresin

LC50/96h 160 mg/l (Leucidus idus)

EC50/48h 220 mg/l (Daphnia magna)

CAS: 68609-97-2 Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives

EbC50/72h 843 mg/l (Pseudokirchneriella subcapitata)

LC50/96h >5000 mg/l (Oncorhynchus mykiss)

(Contd. on page 10)

GB



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 03.10.2025

Version number 35 (replaces version 34)

Revision: 03.10.2025

Trade name MC-DUR ChemProtect AS - Komponente A

(Contd. of page 9)

EC50	1800 mg/l (<i>Lepomis macrochirus</i>)
NOEC	>100 mg/l (BEL) 500 mg/l (<i>Pseudokirchneriella subcapitata</i>)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.
- **Recommended cleaning agent:** Water, if necessary with cleaning agent.

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN3082
- **14.2 UN proper shipping name**
- **ADR, IATA** ENVIRONMENTALLY HAZARDOUS
SUBSTANCE, LIQUID, N.O.S. (epoxide derivates)
- **IMDG** ENVIRONMENTALLY HAZARDOUS
SUBSTANCE, LIQUID, N.O.S. (epoxide derivates),
MARINE POLLUTANT

(Contd. on page 11)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 03.10.2025

Version number 35 (replaces version 34)

Revision: 03.10.2025

Trade name MC-DUR ChemProtect AS - Komponente A

(Contd. of page 10)

· 14.3 Transport hazard class(es)	
· ADR	
· Class	9 (M6) Miscellaneous dangerous substances and articles.
· Label	9
· IMDG, IATA	
· Class	9 Miscellaneous dangerous substances and articles.
· Label	9
· 14.4 Packing group	
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	
· Marine pollutant:	Yes
	Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· Special marking (IATA):	Symbol (fish and tree)
· 14.6 Special precautions for user	
	Warning: Miscellaneous dangerous substances and articles.
· Kemler Number:	90
· EMS Number:	F-A, S-F
· Stowage Category	A
· 14.7 Maritime transport in bulk according to IMO instruments	
	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	(-)
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 12)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 03.10.2025

Version number 35 (replaces version 34)

Revision: 03.10.2025

Trade name MC-DUR ChemProtect AS - Komponente A

(Contd. of page 11)

· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE DERIVATES), 9, III
--------------------------	---

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I

None of the ingredients is listed.

· Seveso category

E2 Hazardous to the Aquatic Environment

· Qualifying quantity (tonnes) for the application of lower-tier requirements

200 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements

500 t

· 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

· Relevant phrases

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

(Contd. on page 13)



BE SURE. BUILD SURE.

Page 13/13

Safety data sheet according to UK REACH

Printing date 03.10.2025

Version number 35 (replaces version 34)

Revision: 03.10.2025

Trade name MC-DUR ChemProtect AS - Komponente A

(Contd. of page 12)

EUH205 Contains epoxy constituents. May produce an allergic reaction.

· **Department issuing data specification sheet:**

Environment protection department.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**

GB