



BE SURE. BUILD SURE.

Page 1/15

## Safety data sheet according to UK REACH

Printing date 03.10.2025

Version number 30 (replaces version 29)

Revision: 03.10.2025

### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### · 1.1 Product identifier

##### · Trade name

**MC-DUR ChemProtect AS - Komponente B**

#### · 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### · Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

##### · Product category

PC9a Coatings and paints, thinners, paint removers

##### · Application of the substance / the mixture

Epoxy coating

#### · 1.3 Details of the supplier of the safety data sheet

##### · Manufacturer/Supplier:

MC-Bauchemie Müller GmbH & Co. KG  
Am Kruppwald 1-8  
D-46238 Bottrop  
Tel.: +49(0)2041-101-0  
Fax.: +49(0)2041-101-400  
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG  
Hagackerstr. 10  
CH-8953 Dietikon  
Tel.: +44-7400510  
Fax : +44-7400533

##### · Informing department:

msds@mc-bauchemie.de

##### · 1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)  
Tel.: +1 872 5888271 (MCR)

### SECTION 2: Hazards identification

#### · 2.1 Classification of the substance or mixture

##### · Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4 H302 Harmful if swallowed.  
Skin Corr. 1B H314 Causes severe skin burns and eye damage.  
Eye Dam. 1 H318 Causes serious eye damage.  
Skin Sens. 1 H317 May cause an allergic skin reaction.  
Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

#### · 2.2 Label elements

##### · Labelling according to

**Regulation (EC) No 1272/2008** The product is classified and labelled according to the GB CLP regulation.

##### · Hazard pictograms



GHS05 GHS07 GHS09

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 03.10.2025

Version number 30 (replaces version 29)

Revision: 03.10.2025

**Trade name MC-DUR ChemProtect AS - Komponente B**

(Contd. of page 1)

- **Signal word** *Danger*
- **Hazard-determining components of labelling:** *benzyl alcohol  
Isophoron Diamine  
Polymer with amino-functional groups  
Tetraethylenepentamine  
2,4,6-Tris-(1-Phenyl-Ethyl) carboic acid  
m-phenylenebis(methylamine)  
2,4,6-tris(dimethylaminomethyl)phenol  
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine  
Triethylenetetramine*
- **Hazard statements** *H302 Harmful if swallowed.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H411 Toxic to aquatic life with long lasting effects.*
- **Precautionary statements** *P260 Do not breathe dusts or mists.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER/doctor.  
P321 Specific treatment (see on this label).  
P362+P364 Take off contaminated clothing and wash it before reuse.*
- **Additional information:** *EUH401 To avoid risks to human health and the environment, comply with the instructions for use.*
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*

### SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** *Resin mixture with colouring agents.  
Mixture consisting of the following components.*

· **Dangerous components:**

<i>CAS: 100-51-6 EINECS: 202-859-9 Reg.nr.: 01-2119492630-38</i>	<i>benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Sens. 1B, H317 ATE: LD50 oral: 1200 mg/kg</i>	<i>30-60%</i>
<i>EC number: 949-140-2</i>	<i>Polymer with amino-functional groups Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317</i>	<i>10-30%</i>

(Contd. on page 3)



BE SURE. BUILD SURE.

Page 3/15

## Safety data sheet according to UK REACH

Printing date 03.10.2025

Version number 30 (replaces version 29)

Revision: 03.10.2025

### Trade name MC-DUR ChemProtect AS - Komponente B

(Contd. of page 2)

CAS: 2855-13-2	Isophoron Diamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317 ATE: LD50 oral: 1030 mg/kg	10-30%
	Polyamine adduct Eye Dam. 1, H318; Skin Irrit. 2, H315	10-30%
CAS: 90640-66-7 EINECS: 292-587-7 Reg.nr.: 01-2119487290-37	Tetraethylenepentamine Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H312; Skin Sens. 1, H317	≥5-<10%
CAS: 61788-44-1 EINECS: 262-975-0	2,4,6-Tris-(1-Phenyl-Ethyl) carbolic acid Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥2.5-<10%
CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50	m-phenylenebis(methylamine) Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥2.5-<5%
CAS: 69-72-7 EINECS: 200-712-3	Salicylic acid Repr. 2, H361d; Eye Dam. 1, H318; Acute Tox. 4, H302	≥1-<1.5%
CAS: 90-72-2	2,4,6-tris(dimethylaminomethyl)phenol Skin Corr. 1C, H314; Eye Dam. 1, H318; Skin Sens. 1, H317	≥1-<1.5%
CAS: 25513-64-8 EINECS: 247-063-2 Reg.nr.: 01-2119560598-25-XXXX	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine Skin Corr. 1A, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317	≥1-<1.5%
CAS: 61788-46-3 Reg.nr.: 2119473798-17	Amines, coco alkyl STOT RE 2, H373; Asp. Tox. 1, H304; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10); Acute Tox. 4, H302; STOT SE 3, H335	≥0.25-<1%
CAS: 90640-67-8 EINECS: 292-588-2	Triethylenetetramine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-<0.5%

· **Additional information**

For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information**

Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.

· **After inhalation**

Supply fresh air; seek medical advice if symptoms occur. If unconscious, place in recovery position and seek medical advice.

· **After skin contact**

In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.

(Contd. on page 4)

GB



BE SURE. BUILD SURE.

Page 4/15

## Safety data sheet according to UK REACH

Printing date 03.10.2025

Version number 30 (replaces version 29)

Revision: 03.10.2025

**Trade name MC-DUR ChemProtect AS - Komponente B**

(Contd. of page 3)

- **After eye contact** *Rinse opened eye for several minutes under running water.  
Call a doctor immediately*
- **After swallowing** *Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.*
- **4.2 Most important symptoms and effects, both acute and delayed** *Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.*

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** *CO2, sand, extinguishing powder. Do not use water.  
Use fire fighting measures that suit the environment.*
- **For safety reasons unsuitable extinguishing agents** *Water.*
- **5.2 Special hazards arising from the substance or mixture** *No further relevant information available.*
- **5.3 Advice for firefighters**
- **Protective equipment:** *No special measures required.*

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** *Wear protective equipment. Keep unprotected persons away.*
- **6.2 Environmental precautions:** *Inform respective authorities in case product reaches water or sewage system.  
Dilute with much water.*
- **6.3 Methods and material for containment and cleaning up:** *Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralising agent.  
Dispose of contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents*
- **6.4 Reference to other sections** *See Section 7 for information on safe handling  
See Section 8 for information on personal protection equipment.  
See Section 13 for information on disposal.*

GB

(Contd. on page 5)



BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 03.10.2025

Version number 30 (replaces version 29)

Revision: 03.10.2025

Trade name **MC-DUR ChemProtect AS - Komponente B**

(Contd. of page 4)

#### SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Open and handle containers with care.  
Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms), because the occupational exposure limit values (see chapter 8) could be exceeded. This must be avoided.  
Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.

· **Information about protection against explosions and fires:**

Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage**

· **Requirements to be met by storerooms and containers:**

No special requirements.

· **Further information about storage conditions:**

Protect from heat and direct sunlight.

· **Storage class**

8A

#### SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Components with critical values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **DNELs**

**CAS: 100-51-6 benzyl alcohol**

Oral	DNEL	4 mg/kg bw/Tag (ArL) 20 mg/kg bw/Tag (Ark)
Dermal	DNEL	8 mg/kg bw/day (ArL) 40 mg/kg bw/day (Ark)
Inhalative	DNEL	22 mg/m <sup>3</sup> (ArL) 110 mg/m <sup>3</sup> (Ark)

**CAS: 2855-13-2 Isophoron Diamine**

Oral	DNEL	0.526 mg/kg bw/Tag (ArL)
------	------	--------------------------

(Contd. on page 6)



BE SURE. BUILD SURE.

**Safety data sheet  
according to UK REACH**

Printing date 03.10.2025

Version number 30 (replaces version 29)

Revision: 03.10.2025

**Trade name MC-DUR ChemProtect AS - Komponente B**

(Contd. of page 5)

Inhalative	DNEL	20.1 mg/m <sup>3</sup> (ArL)
<b>CAS: 1477-55-0 m-phenylenebis(methylamine)</b>		
Dermal	DNEL	0.33 mg/kg bw/day (Workers)
Inhalative	DNEL	1.2 mg/m <sup>3</sup> (Workers)
<b>CAS: 90-72-2 2,4,6-tris(dimethylaminomethyl)phenol</b>		
Inhalative	DNEL	0.31 mg/m <sup>3</sup> (ArL)
<b>· PNECs</b>		
<b>CAS: 100-51-6 benzyl alcohol</b>		
PNEC	0.527 mg/l (Marine water sediment)	
	0.1 mg/l (Mew)	
	1 mg/l (Fresh water sediment)	
PNEC	0.456 mg/kg dwt (Bod)	
	5.27 mg/kg dwt (Fresh water sediment)	
<b>CAS: 2855-13-2 Isophoron Diamine</b>		
PNEC	0.006 mg/l (Mew)	
	0.06 mg/l (Freshwater)	
PNEC	0.578 mg/kg dwt (Sediment)	
	5.784 mg/kg dwt (Fresh water sediment)	
<b>CAS: 1477-55-0 m-phenylenebis(methylamine)</b>		
PNEC	10 mg/l (Kla)	
	0.009 mg/l (Mew)	
	0.094 mg/l (Freshwater)	
PNEC	0.045 mg/kg dwt (Bod)	
	0.43 mg/kg dwt (Marine water sediment)	
	0.43 mg/kg dwt (Fresh water sediment)	
<b>CAS: 90-72-2 2,4,6-tris(dimethylaminomethyl)phenol</b>		
PNEC	0.2 mg/l (Sewage Treatment Plant)	
	0.0084 mg/l (Mew)	
	0.084 mg/l (Freshwater)	
<b>CAS: 25513-64-8 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine</b>		
PNEC	72 mg/l (Sewage Treatment Plant)	
	0.102 mg/l (Fresh water)	
	0.01 mg/l (Mew)	
PNEC	10 mg/kg dwt (Bod)	
	0.062 mg/kg dwt (Sediment)	
	0.622 mg/kg dwt (Fresh water sediment)	

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls**

No further data; see section 7.

(Contd. on page 7)



BE SURE. BUILD SURE.

Page 7/15

## Safety data sheet according to UK REACH

Printing date 03.10.2025

Version number 30 (replaces version 29)

Revision: 03.10.2025

Trade name **MC-DUR ChemProtect AS - Komponente B**

(Contd. of page 6)

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

Keep away from food, drink and animal feed.  
Remove soiled, soaked clothing immediately.  
Wash hands before breaks and at the end of work.  
Avoid contact with eyes and skin.

· **Breathing equipment:**

If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.

· **Hand protection**

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>

For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product

is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.

Nitrile rubber

Recommended material thickness:  $\geq 0.4$  mm

· **Penetration time of glove material**

The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.

Nitrile rubber

Material thickness:  $\geq 0.40$  mm

Penetration time:  $\geq 480$  min

Butyl rubber:

Material thickness:  $\geq 0.5$  mm

Penetration time:  $\geq 480$  min

· **Eye/face protection**

Tight-fitting safety goggles.

Safety goggles.

· **Body protection:**

Protective clothing

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

GB

(Contd. on page 8)



BE SURE. BUILD SURE.

Page 8/15

## Safety data sheet according to UK REACH

Printing date 03.10.2025

Version number 30 (replaces version 29)

Revision: 03.10.2025

Trade name MC-DUR ChemProtect AS - Komponente B

(Contd. of page 7)

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

##### General Information

Physical state	Liquid
Colour:	Ember coloured
Smell:	Amine-like
Odour threshold:	Not determined.
Melting point/freezing point:	Not determined
Boiling point or initial boiling point and boiling range	205.3 °C (CAS: 100-51-6 Benzyl alcohol)
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	1.3 Vol % (CAS: 100-51-6 Benzyl alcohol)
Upper:	13 Vol % (CAS: 100-51-6 Benzyl alcohol)
Flash point:	>100 °C
Auto-ignition temperature:	380 °C (CAS: 2855-13-2 Isophorone diamine)
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
dynamic at 20 °C:	685 mPas
Solubility	
Water:	Fully miscible
Partition coefficient n-octanol/water (log value)	Not determined.
Steam pressure at 20 °C:	0.1 hPa (CAS: 100-51-6 Benzyl alcohol)
Density and/or relative density	
Density at 20 °C	1.05 g/cm <sup>3</sup>
Relative density	Not determined.
Vapour density	Not determined.

#### 9.2 Other information

Appearance:	
Form:	Fluid
Important information on protection of health and environment, and on safety.	
Self-inflammability:	Product is not selfigniting.
Explosive properties:	Product is not explosive.
Change in condition	
Evaporation rate	Not determined.

#### Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void

(Contd. on page 9)

GB



BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 03.10.2025

Version number 30 (replaces version 29)

Revision: 03.10.2025

Trade name MC-DUR ChemProtect AS - Komponente B

(Contd. of page 8)

· <b>Flammable liquids</b>	Void
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

#### SECTION 10: Stability and reactivity

· <b>10.1 Reactivity</b>	No further relevant information available.
· <b>10.2 Chemical stability</b>	stable
· <b>Thermal decomposition / conditions to be avoided:</b>	No decomposition if used according to specifications.
· <b>10.3 Possibility of hazardous reactions</b>	No dangerous reactions known
· <b>10.4 Conditions to avoid</b>	No further relevant information available.
· <b>10.5 Incompatible materials:</b>	No further relevant information available.
· <b>10.6 Hazardous decomposition products:</b>	No dangerous decomposition products known

#### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if swallowed.

· **LD/LC50 values that are relevant for classification:**

**CAS: 100-51-6 benzyl alcohol**

Oral	LD50	1200 mg/kg (ATE) 1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse) 200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)

**CAS: 2855-13-2 Isophoron Diamine**

Oral	LD50	1030 mg/kg (ATE) 1030 mg/kg (rat)
	NOAEL	250 mg/kg (rat)

(Contd. on page 10)



BE SURE. BUILD SURE.

**Safety data sheet  
according to UK REACH**

Printing date 03.10.2025

Version number 30 (replaces version 29)

Revision: 03.10.2025

**Trade name MC-DUR ChemProtect AS - Komponente B**

(Contd. of page 9)

Dermal	LD50	1840 mg/kg (rabbit) >2000 mg/kg (rat) 1840 mg/kg (rabbit)
<b>CAS: 1477-55-0 m-phenylenebis(methylamine)</b>		
Oral	LD50	1180 mg/kg (mouse) 930 mg/kg (rat)
Dermal	LD50	>3100 mg/kg (rabbit)
<b>CAS: 69-72-7 Salicylic acid</b>		
Oral	LD50	891 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
<b>CAS: 90-72-2 2,4,6-tris(dimethylaminomethyl)phenol</b>		
Oral	LD50	mg/kg (rat)
	NOAEL	15 mg/kg (rat)
<b>CAS: 25513-64-8 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine</b>		
Oral	LD50	910 mg/kg (rat)
	NOAEL	10 mg/kg (rat)
<b>CAS: 90640-67-8 Triethylenetetramine</b>		
Oral	LD50	1716 mg/kg (rat)
Dermal	LD50	1465 mg/kg (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

CAS: 61788-44-1	2,4,6-Tris-(1-Phenyl-Ethyl) carboic acid	List II
CAS: 69-72-7	Salicylic acid	List II; III

**SECTION 12: Ecological information**

· **12.1 Toxicity**

· **Aquatic toxicity:**

<b>CAS: 100-51-6 benzyl alcohol</b>		
IC50/72h	700 mg/l (algae)	
LC50/96h	460 mg/l ( <i>Pimephales promelas</i> ) 10 mg/l ( <i>Lepomis macrochirus</i> )	
<b>CAS: 2855-13-2 Isophoron Diamine</b>		
LC50/96h	110 mg/l (fish) 110 mg/l ( <i>Leucidus idus</i> )	

(Contd. on page 11)



BE SURE. BUILD SURE.

**Safety data sheet  
according to UK REACH**

Printing date 03.10.2025

Version number 30 (replaces version 29)

Revision: 03.10.2025

**Trade name MC-DUR ChemProtect AS - Komponente B**

(Contd. of page 10)

EC50	1120 mg/l ( <i>Pseudomonas putida</i> )
EC50/48h	23 mg/l ( <i>daphnia</i> ) 23 mg/l ( <i>Daphnia magna</i> )
NOEC	1.5 mg/l ( <i>Desmodesmus subspicatus</i> ) 3 mg/l ( <i>Daphnia magna</i> )
ErC50/72h	>50 mg/l ( <i>Desmodesmus subspicatus</i> ) >50 mg/l ( <i>algae</i> )
<b>CAS: 1477-55-0 m-phenylenebis(methylamine)</b>	
IC50/72h	12 mg/l ( <i>algae</i> )
EC50/72h	12 mg/l ( <i>Scenedesmus subspicatus</i> )
LC50/96h	>100 mg/l ( <i>Oncorhynchus mykiss</i> ) 87.6 mg/l ( <i>Ory</i> )
EC50/48h	15.2 mg/l ( <i>Daphnia magna</i> )
<b>CAS: 90-72-2 2,4,6-tris(dimethylaminomethyl)phenol</b>	
EC50/72h	84 mg/l ( <i>Desmodesmus subspicatus</i> )
LC50/96h	175 mg/l ( <i>Cyp</i> ) 718 mg/l ( <i>Daphnia magna</i> )
NOEC	2 mg/l ( <i>BEL</i> ) 6.25 mg/l ( <i>Desmodesmus subspicatus</i> )
<b>CAS: 25513-64-8 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine</b>	
EC50/24h	31.5 mg/l ( <i>Daphnien</i> )
EC50	89 mg/l ( <i>Pseudomonas putida</i> )
LC50/48h	174 mg/l ( <i>Leucidus idus</i> )
NOEC	10.9 mg/l ( <i>Danio rerio</i> ) 16 mg/l ( <i>Pseudokirchneriella subcapitata</i> ) 1.02 mg/l ( <i>Daphnia magna</i> )
ErC50/72h	43.5 mg/l ( <i>Pseudokirchneriella subcapitata</i> )

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:** Must not reach sewage water or drainage ditch undiluted or unneutralised.

(Contd. on page 12)





BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 03.10.2025

Version number 30 (replaces version 29)

Revision: 03.10.2025

**Trade name MC-DUR ChemProtect AS - Komponente B**

(Contd. of page 12)

· <b>Segregation Code</b>	SG35 Stow "separated from" SGG1-acids
· <b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	E
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. ( T E T R A E T H Y L E N E P E N T A M I N E , ISOPHORONEDIAMINE), 8, II

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I**

None of the ingredients is listed.

· **Seveso category**

E2 Hazardous to the Aquatic Environment

· **Qualifying quantity (tonnes) for the application of lower-tier requirements**

200 t

(Contd. on page 14)



BE SURE. BUILD SURE.

### Safety data sheet according to UK REACH

Printing date 03.10.2025

Version number 30 (replaces version 29)

Revision: 03.10.2025

**Trade name MC-DUR ChemProtect AS - Komponente B**

(Contd. of page 13)

· **Qualifying quantity (tonnes)  
for the application of upper-  
tier requirements**

500 t

· **15.2 Chemical safety  
assessment:**

A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

· **Relevant phrases**

H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H361d Suspected of damaging the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

· **Department issuing data  
specification sheet:**

Environment protection department.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation  
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
DNEL: Derived No-Effect Level (UK REACH)  
PNEC: Predicted No-Effect Concentration (UK REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
ATE: Acute toxicity estimate values  
Acute Tox. 4: Acute toxicity – Category 4  
Skin Corr. 1A: Skin corrosion/irritation – Category 1A  
Skin Corr. 1B: Skin corrosion/irritation – Category 1B  
Skin Corr. 1C: Skin corrosion/irritation – Category 1C  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
Skin Sens. 1: Skin sensitisation – Category 1

(Contd. on page 15)



BE SURE. BUILD SURE.

Page 15/15

## Safety data sheet according to UK REACH

Printing date 03.10.2025

Version number 30 (replaces version 29)

Revision: 03.10.2025

**Trade name MC-DUR ChemProtect AS - Komponente B**

(Contd. of page 14)

*Skin Sens. 1A: Skin sensitisation – Category 1A*

*Skin Sens. 1B: Skin sensitisation – Category 1B*

*Repr. 2: Reproductive toxicity – Category 2*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

*STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2*

*Asp. Tox. 1: Aspiration hazard – Category 1*

*Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1*

*Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1*

*Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*

*Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

**\* Data compared to the  
previous version altered.**

GB