



BE SURE. BUILD SURE.

Page 1/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.09.2025

Version number 33 (replaces version 32)

Revision: 26.09.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name **MC-Quicksolid komp. B**

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Application of the substance

/ the mixture Polyurethane resin
Adhesives

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

· Informing department: msds@mc-bauchemie.de

· 1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Carc. 2 H351 Suspected of causing cancer.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

· 2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

IE

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.09.2025

Version number 33 (replaces version 32)

Revision: 26.09.2025

Trade name MC-Quicksolid komp. B

(Contd. of page 1)

· Hazard pictograms



GHS07 GHS08

· Signal word

Danger

· Hazard-determining components of labelling:

*Diphenylmethane diisocyanate, isomers and homologues
3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, oligomers*

*diphenylmethane-4,4'-di-isocyanate
p-toluenesulphonyl isocyanate*

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

· Additional information:

EUH204 Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before industrial or professional use.

· Labelling of packages where the contents do not exceed 125 ml

· Hazard pictograms



GHS07 GHS08

· Signal word

Danger

· Hazard-determining components of labelling:

Diphenylmethane diisocyanate, isomers and homologues

3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, oligomers

(Contd. on page 3)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.09.2025

Version number 33 (replaces version 32)

Revision: 26.09.2025

Trade name MC-Quicksolid komp. B

(Contd. of page 2)

- **Hazard statements**
 - diphenylmethane-4,4'-di-isocyanate
 - p-toluenesulphonyl isocyanate
 - H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 - H317 May cause an allergic skin reaction.
 - H351 Suspected of causing cancer.
- **Precautionary statements**
 - P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 - P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 - P284 [In case of inadequate ventilation] wear respiratory protection.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 9016-87-9 EC number: 618-498-9	Diphenylmethane diisocyanate, isomers and homologues Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	50-70%
CAS: 53880-05-0	3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, oligomers Skin Sens. 1, H317, EUH204	≥1-<10%

(Contd. on page 4)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.09.2025

Version number 33 (replaces version 32)

Revision: 26.09.2025

Trade name MC-Quicksolid komp. B

(Contd. of page 3)

<p>CAS: 101-68-8 EINECS: 202-966-0 Reg.nr.: 01-2119457014-47</p>	<p><i>diphenylmethane-4,4'-di-isocyanate</i> Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %</p>	<p>≥1-<2.5%</p>
<p>CAS: 4083-64-1 EINECS: 223-810-8</p>	<p><i>p-toluenesulphonyl isocyanate</i> Resp. Sens. 1, H334; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335, EUH014, EUH204 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % STOT SE 3; H335: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 %</p>	<p>≥0.1-<0.5%</p>

· **Additional information**

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information**

Remove, decontaminate and dispose of soiled, soaked clothing and shoes immediately.

· **After inhalation**

Remove person to fresh air, keep warm, allow to rest; if breathing is difficult, seek medical attention.

· **After skin contact**

In case of contact with skin, preferably wash with polyethylene glycol-based cleaner or clean with plenty of warm water and soap. Consult a doctor in case of skin reactions.

· **After eye contact**

Rinse the eyes with open eyelids for a sufficiently long time (at least 10 minutes) with water that is as lukewarm as possible. Consult an ophthalmologist.

· **After swallowing**

Do NOT induce vomiting. Rinse mouth with water. Medical attention required.

· **4.2 Most important symptoms and effects, both acute and delayed**

Information for the doctor: The product irritates the respiratory tract and is a potential trigger for skin and respiratory sensitisation. Treatment of acute irritation or bronchial constriction is primarily symptomatic. Depending on the extent of exposure and the symptoms, prolonged medical treatment may be necessary.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No information available.



BE SURE. BUILD SURE.

Page 5/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.09.2025

Version number 33 (replaces version 32)

Revision: 26.09.2025

Trade name MC-Quicksolid komp. B

(Contd. of page 4)

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Put on breathing apparatus.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:** Prevent material from reaching sewage system, holes and cellars.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure sufficient air exchange and/or extraction in the work areas.
Air extraction is required for spray application.
For solid products: Avoid dust formation and dust deposits.
Air limit values mentioned in section 8 must be monitored.
At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being exceeded. The air must be moved away from people.
For products containing solvents: Explosion protection required.
The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes and inhalation of vapours.
Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing immediately.

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.09.2025

Version number 33 (replaces version 32)

Revision: 26.09.2025

Trade name MC-Quicksolid komp. B

(Contd. of page 5)

Open and handle container with care.

7.2 Conditions for safe storage, including any incompatibilities

Keep container dry and tightly closed. Further information on the storage conditions that must be observed for quality assurance reasons can be found in our technical data sheet.

Storage

Requirements to be met by storerooms and containers:

Store only in the original container.

Further information about storage conditions:

None.

Storage class

10

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with critical values that require monitoring at the workplace:

CAS: 9016-87-9 Diphenylmethane diisocyanate, isomers and homologues

OEL (Ireland)	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ as -NCO; Sens.
---------------	---

CAS: 101-68-8 diphenylmethane-4,4'-di-isocyanate

OEL (Ireland)	Long-term value: 0.005 ppm as -NCO; Sens
---------------	---

CAS: 4083-64-1 p-toluenesulphonyl isocyanate

OEL (Ireland)	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ as -NCO; Sens.
---------------	---

DNELs

CAS: 9016-87-9 Diphenylmethane diisocyanate, isomers and homologues

Inhalative	DNEL	0.05 mg/m ³ (ArL)
------------	------	------------------------------

CAS: 101-68-8 diphenylmethane-4,4'-di-isocyanate

Dermal	DNEL	50 mg/kg bw/day (Ark)
Inhalative	DNEL	0.05 mg/m ³ (ArL)

PNECs

CAS: 9016-87-9 Diphenylmethane diisocyanate, isomers and homologues

PNEC	1 mg/l (Sewage Treatment Plant)	
	0.1 mg/l (Mew)	
	1 mg/l (Freshwater)	
PNEC	1 mg/kg dwt (Bod)	

(Contd. on page 7)



BE SURE. BUILD SURE.

Page 7/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.09.2025

Version number 33 (replaces version 32)

Revision: 26.09.2025

Trade name MC-Quicksolid komp. B

(Contd. of page 6)

CAS: 101-68-8 diphenylmethane-4,4'-di-isocyanate

PNEC 1 mg/l (Sewage Treatment Plant)

0.1 mg/l (Mew)

1 mg/l (Freshwater)

PNEC 1 mg/kg dwt (Bod)

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls**

No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

Keep away from food, drink and animal feed.
Remove soiled, soaked clothing immediately.
Wash hands before breaks and at the end of work.
Avoid contact with eyes and skin.

· **Breathing equipment:**

Respiratory protection required at insufficiently ventilated workplaces and when working with splashes. Fresh air masks or combination filters A2-P2 (EN529) are recommended for short-term work.

If applicable, further recommendations for respiratory protection can be found in the appendix.

In case of hypersensitivity of the respiratory tract (asthma, chronic bronchitis), handling of the product is not recommended.

· **Hand protection**

Suitable materials for protective gloves; EN 374:

Butyl rubber, nitrile rubber, chloroprene rubber (neoprene).

Note: suitable materials that provide sufficient protection for industrial cleaning with aprotic polar solvents (according to IUPAC definition): butyl rubber.

In case of prolonged or frequently repeated contact, a glove with a protection class of 5 or higher is recommended (breakthrough time greater than 240 minutes according to EN374). For short-term contact, a glove with a protection class of 3 or higher is recommended (breakthrough time greater than 60 minutes according to EN374).

The thickness of the material is not the only criterion for the level of protection of a glove against a chemical substance. The protective effect also depends to a large extent on the type of glove material. Depending on the type and material, the thickness must be more than 0.35 mm to ensure adequate protection in the event of prolonged and frequent contact. Exceptions to this rule are multi-layer gloves, which guarantee sufficient protection even with a thickness of less than 0.35 mm during prolonged wear. Other glove materials with a thickness of less than 0.35 mm only provide sufficient protection for short periods of wear.

For solvent-free products:

Example:

Polychloroprene - CR: thickness ≥ 0.5 mm; breakthrough time ≥ 480 min.

(Contd. on page 8)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.09.2025

Version number 33 (replaces version 32)

Revision: 26.09.2025

Trade name MC-Quicksolid komp. B

(Contd. of page 7)

- **Material of gloves**
Nitrile rubber - NBR: thickness $\geq 0.35\text{mm}$; breakthrough time $\geq 480\text{min}$.
Butyl rubber - IIR: thickness $\geq 0.5\text{mm}$; breakthrough time $\geq 480\text{min}$.
Fluoro rubber - FKM: thickness $\geq 0.4\text{mm}$; breakthrough time $\geq 480\text{min}$.
Recommendation: Dispose of contaminated gloves.
Polychloroprene - CR
Nitrile rubber - NBR
Butyl rubber - IIR
Fluoro rubber - FKM
- **Penetration time of glove material**
Polychloroprene - CR: thickness $\geq 0.5\text{mm}$; breakthrough time $\geq 480\text{min}$.
Nitrile rubber - NBR: thickness $\geq 0.35\text{mm}$; breakthrough time $\geq 480\text{min}$.
Butyl rubber - IIR: thickness $\geq 0.5\text{mm}$; breakthrough time $\geq 480\text{min}$.
Fluoro rubber - FKM: Thickness $\geq 0.4\text{mm}$; Breakthrough time $\geq 480\text{min}$.
- **Eye/face protection**
Safety goggles with side protection in accordance with EN 166.
- **Body protection:**
Use chemical-resistant protective clothing.
In case of hypersensitivity of the skin, handling the product is not recommended.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Colour:** Yellowish
- **Smell:** Characteristic
- **Melting point/freezing point:** Not determined
- **Boiling point or initial boiling point and boiling range** Not determined
- **Flash point:** $>150\text{ }^\circ\text{C}$
- **Auto-ignition temperature:** $400\text{ }^\circ\text{C}$
- **pH** Not determined.
- **Viscosity:**
- **Kinematic viscosity** Not determined.
- **dynamic at $20\text{ }^\circ\text{C}$:** $5200\text{-}7800\text{ mPas}$
- **Solubility**
- **Water:** Not miscible or difficult to mix
- **Steam pressure:** Not determined.
- **Density and/or relative density**
- **Density at $20\text{ }^\circ\text{C}$** 1.31 g/cm^3

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.09.2025

Version number 33 (replaces version 32)

Revision: 26.09.2025

Trade name MC-Quicksolid komp. B

(Contd. of page 8)

· **9.2 Other information**

· **Appearance:**

· **Form:**

Pasty

· **Important information on protection of health and environment, and on safety.**

· **Self-inflammability:**

Product is not selfigniting.

· **Explosive properties:**

Product is not explosive.

· **Information with regard to physical hazard classes**

· **Explosives**

Void

· **Flammable gases**

Void

· **Aerosols**

Void

· **Oxidising gases**

Void

· **Gases under pressure**

Void

· **Flammable liquids**

Void

· **Flammable solids**

Void

· **Self-reactive substances and mixtures**

Void

· **Pyrophoric liquids**

Void

· **Pyrophoric solids**

Void

· **Self-heating substances and mixtures**

Void

· **Substances and mixtures, which emit flammable gases in contact with water**

Void

· **Oxidising liquids**

Void

· **Oxidising solids**

Void

· **Organic peroxides**

Void

· **Corrosive to metals**

Void

· **Desensitised explosives**

Void

SECTION 10: Stability and reactivity

· **10.1 Reactivity**

No further relevant information available.

· **10.2 Chemical stability**

· **Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions**

Reacts with amines

· **10.4 Conditions to avoid**

No further relevant information available.

· **10.5 Incompatible materials:**

No further relevant information available.

· **10.6 Hazardous**

decomposition products:

No dangerous decomposition products known



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.09.2025

Version number 33 (replaces version 32)

Revision: 26.09.2025

Trade name MC-Quicksolid komp. B

(Contd. of page 9)

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:

CAS: 9016-87-9 Diphenylmethane diisocyanate, isomers and homologues

Oral	LD50	>10000 mg/kg (Rat)
------	------	--------------------

Dermal	LD50	>5000 mg/kg (Rab)
--------	------	-------------------

Inhalative	LC50/4 h	~450 mg/l (Rat)
------------	----------	-----------------

CAS: 101-68-8 diphenylmethane-4,4'-di-isocyanate

Oral	LD50	>10000 mg/kg (rat)
------	------	--------------------

Dermal	LD50	>9400 mg/kg (rabbit)
--------	------	----------------------

CAS: 4083-64-1 p-toluenesulphonyl isocyanate

Oral	LD50	2600 mg/kg (rat)
------	------	------------------

Primary irritant effect:

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitisation May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Suspected of causing cancer.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure May cause respiratory irritation.

STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

CAS: 556-67-2	octamethylcyclotetrasiloxane	List II
---------------	------------------------------	---------

CAS: 108-90-7	chlorobenzene	List II
---------------	---------------	---------

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

CAS: 101-68-8 diphenylmethane-4,4'-di-isocyanate

EC50/24h	>1000 mg/l (Daphnia magna)
----------	----------------------------

LC50/96h	>1000 mg/l (Brachydanio rerio)
----------	--------------------------------

NOEC	>1000 mg/l (Eisenia foetida)
------	------------------------------

	>10 mg/l (Daphnia magna)
--	--------------------------

(Contd. on page 11)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.09.2025

Version number 33 (replaces version 32)

Revision: 26.09.2025

Trade name MC-Quicksolid komp. B

(Contd. of page 10)

- **12.2 Persistence and degradability** *No further relevant information available.*
- **12.3 Bioaccumulative potential** *No further relevant information available.*
- **12.4 Mobility in soil** *No further relevant information available.*
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*
- **12.6 Endocrine disrupting properties** *For information on endocrine disrupting properties see section 11.*
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** *Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.*

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** *Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*

· **European waste catalogue**

HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP7	Carcinogenic
HP13	Sensitising

- **Uncleaned packagings:**
- **Recommendation:** *Disposal must be made according to official regulations.*

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, ADN, IMDG, IATA** *Void*
- **14.2 UN proper shipping name**
- **ADR, ADN, IMDG, IATA** *Void*
- **14.3 Transport hazard class(es)**
- **ADR, ADN, IMDG, IATA**
- **Class** *Void*
- **14.4 Packing group**
- **ADR, IMDG, IATA** *Void*
- **14.5 Environmental hazards:**
- **Marine pollutant:** *No*

(Contd. on page 12)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.09.2025

Version number 33 (replaces version 32)

Revision: 26.09.2025

Trade name MC-Quicksolid komp. B

(Contd. of page 11)

- **14.6 Special precautions for user** *Not applicable.*
- **14.7 Maritime transport in bulk according to IMO instruments** *Not applicable.*
- **UN "Model Regulation":** *Void*

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture** *No further relevant information available.*
- **REGULATION (EC) No 1907/2006 ANNEX XVII** *Conditions of restriction: 3, 56a, 74*

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**
None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**
None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**
None of the ingredients is listed.

· **Regulation (EC) No 273/2004 on drug precursors**
None of the ingredients is listed.

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**
None of the ingredients is listed.

· **15.2 Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
 - H315 *Causes skin irritation.*
 - H317 *May cause an allergic skin reaction.*
 - H319 *Causes serious eye irritation.*
 - H332 *Harmful if inhaled.*
 - H334 *May cause allergy or asthma symptoms or breathing difficulties if inhaled.*
 - H335 *May cause respiratory irritation.*

(Contd. on page 13)



BE SURE. BUILD SURE.

Page 13/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.09.2025

Version number 33 (replaces version 32)

Revision: 26.09.2025

Trade name MC-Quicksolid komp. B

(Contd. of page 12)

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

EUH014 Reacts violently with water.

EUH204 Contains isocyanates. May produce an allergic reaction.

· **Department issuing data specification sheet:**

Environment protection department.

· **Date of previous version:**

20.10.2021

· **Version number of previous version:**

32

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

· *** Data compared to the previous version altered.**

IE