

# Mycoflex Fugenfüller PE

Round profile of closed-cell expanded polyethylene



## PRODUCT PROPERTIES

- Closed-cell polyethylene-foam
- Flexible
- Water- and moisture repellent
- Resistant to age
- Insertable with all Mycoflex-sealants

## AREAS OF APPLICATION

- Firming of powdery and dusty substrates
- Primer for the Nafuflex-sealing system
- Sealing of finely-porous, moist concrete and plaster surfaces and pre-cast elements

## APPLICATION ADVICE

Following substrate preparation of the joint flanks, Mycoflex Fugenfüller PE is pressed into the joint using a suitable blunt tool. The insertion depth of the joint filler must comply with standards or guidelines applicable for the respective area of application. The diameter of the joint filler should exceed the width of the joint by approx. 25 - 30 %.

Colour	grey
Delivery form	Ø 6 mm: box à 100 m Ø 10 mm: box à 100 m Ø 15 mm: box à 100 m Ø 20 mm: box à 50 m Ø 25 mm: box à 50 m Ø 30 mm: box à 25 m Ø 40 mm: 1 m - bar Ø 50 mm: 1 m - bar
Storage	Can be stored in cool and dry conditions for at least 12 months in original unopened packs.

## Safety instructions

Please note the safety information and advice given on the packaging labels and safety data sheets.

**Note:** The information contained in this data sheet is based on our experience and is correct to the best of our knowledge. It is, however, not binding. It will need to be adapted to the requirements of the individual structure, to the specific application and to non-standard local conditions. Application-specific conditions must be checked in advance by the planning engineer/specifier and, where different from the standard conditions indicated, will require individual approval. Technical advice provided by MC's specialist consultants does not replace the need for a planning review by the client or its agents in respect of the history of the building or structure. Subject to this prerequisite, we are liable for the correctness of this information within the framework of our terms and conditions of sale and delivery. Recommendations of our employees deviating from the information given in our data sheets are only binding for us if they are confirmed in writing. In all cases, the generally accepted rules and practices reflecting the current state of the art must be observed. The information given in this technical data sheet is valid for the product supplied by the country company listed in the footer. It should be noted that data in other countries may differ. The product data sheets valid for the relevant foreign country must be observed. The latest technical data sheet shall apply to the exclusion of previous, duly superseded versions; the date of issue in the footer must be observed. The latest version is available from us on request or may be downloaded from our website. [2300018271]